



MPM Motor Oil SAE 20W-20 Super Single Grade

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 5-3-2020 Revision date: 20-12-2022 Supersedes: 27-8-2020 version: 5.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : MPM Motor Oil SAE 20W-20 Super Single Grade
Product code : 41000B
Type of product : Other engine, gear and lubricating oils.
Product group : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Consumer use, Industrial use
Industrial/Professional use spec : Non-dispersive use
Used in closed systems
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

MPM International Oil Company BV
Cyclotronweg 1
2629 HN Delft - Nederland
T +31 (0)15 2514030
info@mpmoil.com - www.mpmoil.com

1.4. Emergency telephone number

Emergency number : +31 (0)15 2514030 (08.00 - 17.00 GMT+1)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

MPM Motor Oil SAE 20W-20 Super Single Grade

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains: Sulfonic acids, petroleum, calcium salts. May produce an allergic reaction.
EUH210 - Safety data sheet available on request.

2.3. Other hazards

Other hazards not contributing to the classification : Combustible liquids. Spills of this product present a serious slipping hazard.

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments : Highly refined mineral oil, contains <3% (w/w) DMSO extract, according to IP346

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (Note L)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8	$\geq 50 - \leq 75$	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (Note L)	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6 REACH-no: 01-2119471299-27	$\geq 20 - \leq 50$	Not classified
Sulfonic acids, petroleum, calcium salts	CAS-No.: 61789-86-4 EC-No.: 263-093-9 REACH-no: 01-2119488992-18	< 0,2	Skin Sens. 1B, H317

Note L - The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.

Full text of H- and EUH-statements: see section 16

MPM Motor Oil SAE 20W-20 Super Single Grade

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation	: Not required.
After skin contact	: Wash skin with mild soap and water.
After eye contact	: In case of eye contact, immediately rinse with clean water for 10-15 minutes.
After ingestion	: Do NOT induce vomiting. Rinse mouth out with water. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

After inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
After skin contact	: Not expected to present a significant skin hazard under anticipated conditions of normal use.
After eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
After ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray, powder, foam and CO ₂ .
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Precautionary measures fire	: Exercise caution when fighting any chemical fire.
Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : If spilled, may cause the floor to be slippery.

6.1.1. For non-emergency personnel

Protective equipment	: Gloves. Safety glasses.
Emergency procedures	: Do not breathe vapours.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing and gloves. Safety glasses.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Detergent. Clean up any spills as soon as possible, using an absorbent material to collect it.
Other information	: Spill area may be slippery. Use suitable disposal containers.

MPM Motor Oil SAE 20W-20 Super Single Grade

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Avoid all unnecessary exposure. Both local exhaust and general room ventilation are usually required.
Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Handling temperature	: < 40 °C
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Store in a closed container.
Storage conditions	: Keep container closed when not in use.
Storage temperature	: ≤ 40 °C
Storage area	: Store in dry, well-ventilated area.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

EU - Indicative Occupational Exposure Limit (IOEL)

IOELV TWA (mg/m ³)	5 mg/m ³
IOELV STEL (mg/m ³)	10 mg/m ³

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

Additional information : Based on ACGIH TLV, a concentration of 5 mg/m³ oilspray (TWA, 8 hour workday) is recommended.

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Technical measures:

No additional information available.

MPM Motor Oil SAE 20W-20 Super Single Grade

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Safety glasses.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety goggles

8.2.2.2. Skin protection

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use

Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,4		EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid.
Colour	: Amber.
Appearance	: Oily liquid.
Odour	: Characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: < -30 °C @ ASTM D7346
Boiling point	: Not available
Flammability	: Not available
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 201 °C @ ASTM D92
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 66 mm ² /s @ 40°C (ASTM D7042)
Solubility	: Slightly soluble, the product remains on the water surface.
Log Kow	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available

MPM Motor Oil SAE 20W-20 Super Single Grade

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Density	: 887 kg/m ³ @ 15°C
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal conditions.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

No naked flames, sparks, and do not smoke.

10.5. Incompatible materials

Strong oxidizing agent. Acids and bases.

10.6. Hazardous decomposition products

None under normal conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

LD50 oral rat	> 5000 mg/kg bodyweight
LD50 oral	> 5000 mg/kg
LC50 Inhalation - Rat	> 5,53 mg/l/4h

MPM Motor Oil SAE 20W-20 Super Single Grade

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Sulfonic acids, petroleum, calcium salts (61789-86-4)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 4000 mg/kg
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met.) (Based on available data, the classification criteria are not met.)
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

LOAEL (oral, rat)	125 mg/kg bodyweight
NOAEL (dermal, rat/rabbit)	≈ 1000 mg/kg bodyweight
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

MPM Motor Oil SAE 20W-20 Super Single Grade

Viscosity, kinematic	66 mm ² /s @ 40°C (ASTM D7042)
----------------------	---

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

11.2.2. Other information

SECTION 12: Ecological information

12.1. Toxicity

General	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

LC50 fish 1	100 mg/l
EC50 Daphnia 1	10000 mg/l
EC50 72h - Algae [1]	3 mg/l

Sulfonic acids, petroleum, calcium salts (61789-86-4)

LC50 fish 1	> 1000 mg/l
-------------	-------------

MPM Motor Oil SAE 20W-20 Super Single Grade

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Sulfonic acids, petroleum, calcium salts (61789-86-4)

EC50 Daphnia 1	> 1000 mg/l
----------------	-------------

12.2. Persistence and degradability

MPM Motor Oil SAE 20W-20 Super Single Grade

Persistence and degradability	Not soluble in water, so only minimally biodegradable.
-------------------------------	--

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

Persistence and degradability	The product is not biodegradable.
-------------------------------	-----------------------------------

Biodegradation	31 % 28 d OECD 301F
----------------	---------------------

12.3. Bioaccumulative potential

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

Bioconcentration factor (BCF REACH)	260
-------------------------------------	-----

Log Pow	9,2
---------	-----

12.4. Mobility in soil

MPM Motor Oil SAE 20W-20 Super Single Grade

Soil	Prevent soil and water pollution.
------	-----------------------------------

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The product does not contain any substances with endocrine disrupting properties.

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Additional information : This material and its container must be disposed of in a safe way, and as per local legislation.
European List of Waste (LoW, EC 2000/532) : 13 02 05* - mineral-based non-chlorinated engine, gear and lubricating oils

SECTION 14: Transport information

In accordance with ADR / IMDG

14.1. UN number or ID number

UN-No. : Not regulated
UN-No. (IMDG) : Not regulated

MPM Motor Oil SAE 20W-20 Super Single Grade

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.2. UN proper shipping name

Proper Shipping Name (ADR) : Not regulated
Proper Shipping Name (IMDG) : Not regulated

14.3. Transport hazard class(es)

ADR
Transport hazard class(es) (ADR) : Not regulated

IMDG
Transport hazard class(es) (IMDG) : Not regulated

14.4. Packing group

Packing group (ADR) : Not regulated
Packing group (IMDG) : Not regulated

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available

14.6. Special precautions for user

Overland transport
Not regulated

Transport by sea
Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)
Contains no substance(s) listed on the REACH Candidate List
Contains no substance(s) listed on REACH Annex XIV (Authorisation List)
Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)
Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Indication of changes

Section	Changed item	Change	Comments
	Supersedes	Modified	
	Revision date	Modified	

MPM Motor Oil SAE 20W-20 Super Single Grade

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes			
Section	Changed item	Change	Comments
	Adverse effects on the environment caused by endocrine disrupting properties	Added	
	Type of product	Added	
1.1	Trade name	Added	
1.1	Product group	Added	
1.2	Industrial/Professional use spec	Added	
1.2	Main use category	Modified	
2.2	EUH-statements	Added	
2.3	Other hazards not contributing to the classification	Added	
3	Composition/information on ingredients	Modified	
4.1	After skin contact	Modified	
4.1	After inhalation	Modified	
4.1	After ingestion	Modified	
4.2	After skin contact	Added	
4.2	After inhalation	Added	
4.2	After ingestion	Added	
4.2	After eye contact	Added	
5.1	Suitable extinguishing media	Modified	
5.3	Precautionary measures fire	Added	
5.3	Firefighting instructions	Added	
6.1	Emergency procedures	Added	
6.1	General measures	Added	
6.1	Protective equipment	Modified	
6.1	Protective equipment	Modified	
6.2	Environmental precautions	Modified	
6.3	Methods for cleaning up	Modified	
6.3	Other information	Modified	
7.1	Additional hazards when processed	Added	
7.1	Precautions for safe handling	Modified	
7.1	Hygiene measures	Modified	
7.2	Technical measures	Added	
7.2	Storage conditions	Added	
7.2	Storage temperature	Modified	
7.2	Storage area	Modified	
8.2	Technical measures	Added	
8.2	Respiratory protection	Modified	
8.2	Hand protection	Modified	
9.1	Freezing point	Added	

MPM Motor Oil SAE 20W-20 Super Single Grade

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes			
Section	Changed item	Change	Comments
9.1	Appearance	Modified	
9.1	Viscosity, kinematic	Modified	
9.1	Density	Modified	
9.1	Flash point	Modified	
10.2	Chemical stability	Added	
10.3	Possibility of hazardous reactions	Added	
10.4	Conditions to avoid	Added	
10.5	Incompatible materials	Modified	
10.6	Hazardous decomposition products	Added	
11.1	Reason for no classification	Added	
12.1	General	Modified	
12.4	Soil	Added	
13.1	Additional information	Added	
13.1	European List of Waste (LoW, EC 2000/532)	Added	

Full text of H- and EUH-statements	
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains: Sulfonic acids, petroleum, calcium salts. May produce an allergic reaction.
EUH210	Safety data sheet available on request.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
Skin Sens. 1B	Skin sensitisation, category 1B

SDS MPM REACH

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.