

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : QUARTZ 9000 FUTURE GF6 0W-20
Product code : 091127
Product description : Not available.
Product type : Liquid.
Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Engine oil
Formulation additives, lubricants and greases - Industrial
General use of lubricants and greases in vehicles or machinery - Industrial
General use of lubricants and greases in vehicles or machinery - Professional

Uses advised against

Not applicable.

1.3 Details of the supplier of the safety data sheet

TotalEnergies Lubrifiants
562 Avenue du Parc de L'île
92029 Nanterre Cedex FRANCE
Tél: +33 (0)1 41 35 40 00
Fax: +33 (0)1 41 35 84 71
rm.msds-lubs@totalenergies.com

TotalEnergies Marketing UK Limited
10 Upper Bank Street (19th floor)
Canary Wharf,
London E14 5BF
UNITED KINGDOM
Tel: +44 (0)20 7339 8000
Fax: +44 (0)20 7339 8033
rm.gb-msds@totalenergies.com

H.S.E

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : National Poisons Information Service (NPIS): 111

Supplier

Telephone number : Emergency telephone: +44 1235 239670

Hours of operation : Edit the content of sentence <GB Telephone Number - Supplier - Hours of operation> to define this output

Information limitations : Edit the content of sentence <GB Telephone Number - Supplier - Information limitations> to define this output


SECTION 1: Identification of the substance/mixture and of the company/undertaking


SECTION 2: Hazards identification


2.1 Classification of the substance or mixture


Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

 Skin Sens. 1, H317

 The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

Ingredients of unknown toxicity :  7 percent of the mixture consists of component(s) of unknown acute dermal toxicity

Ingredients of unknown ecotoxicity :  Contains 3.1% of components with unknown hazards to the aquatic environment

See Section 16 for the full text of the H statements declared above.


See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements


Hazard pictograms :





Signal word :  Warning

Hazard statements :  H317 - May cause an allergic skin reaction.


Precautionary statements

General :  P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P103 - Read carefully and follow all instructions.

Prevention :  P261 - Avoid breathing gas, vapour or spray.
P280 - Wear protective gloves.

Response :  P362 + P364 - Take off contaminated clothing and wash it before reuse.
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.

Storage :  Not applicable.

Disposal :  P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains :  dihydro-3-(2-octadecenyl)furan-2,5-dione

Supplemental label elements :  Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

2.3 Other hazards

SECTION 2: Hazards identification

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration $\geq 0,1\%$.
This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

Other hazards which do not result in classification

: Hazard of slipping on spilt product.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
Distillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 EC: 265-157-1 CAS: 64742-54-7 Index: 649-467-00-8	$\geq 75 - \leq 90$	Asp. Tox. 1, H304	[1]
Distillates (petroleum), solvent-dewaxed heavy paraffinic	REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6	≤ 3	Asp. Tox. 1, H304	[1]
Distillates (petroleum), solvent-dewaxed light paraffinic	REACH #: 01-2119480132-48 EC: 265-159-2 CAS: 64742-56-9 Index: 649-469-00-9	≤ 3	Asp. Tox. 1, H304	[1]
Distillates (petroleum), hydrotreated light paraffinic	REACH #: 01-2119487077-29 EC: 265-158-7 CAS: 64742-55-8	≤ 3	Asp. Tox. 1, H304	[1]
Distillates (petroleum), solvent-refined light paraffinic	REACH #: 01-2119487067-30 EC: 265-091-3 CAS: 64741-89-5	≤ 3	Asp. Tox. 1, H304	[1]
dihydro-3-(2-octadecenyl)furan-2,5-dione	REACH #: 01-2120120387-61 EC: 701-338-8 CAS: 67066-88-0	< 1	Skin Irrit. 2, H315 Skin Sens. 1A, H317 See Section 16 for the full text of the H statements declared above.	[1]

Additional information : Mineral oil of petroleum origin Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 3: Composition/information on ingredients

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products : carbon monoxide
carbon dioxide
nitrogen oxides
sulfur oxides
Hydrogen sulfide
Mercaptans
Zinc oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

SECTION 6: Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Reportable hazardous constituent(s) contained in UVCB- and/or multi-constituent substance(s) complying with the classification criteria and/or with an exposure limit (OEL)

No exposure limit value known.

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Advisory OEL : Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined)

DNELs/DMELs

Product/substance	Type	Exposure	Value	Population	Effects
Distillates (petroleum), hydrotreated heavy paraffinic	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
Distillates (petroleum), solvent-dewaxed heavy paraffinic	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
Distillates (petroleum), solvent-dewaxed light paraffinic	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
Distillates (petroleum), hydrotreated light paraffinic	DNEL	Long term Inhalation	5.4 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	1.2 mg/m ³	General population	Local
	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m ³	General population	Local
OTHER LUBRICANT BASE OILS	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	5.4 mg/m ³	Workers	Local

SECTION 8: Exposure controls/personal protection

IP 346 < 3% w/w; Viscosity ≤ 20.5 mm²/s at 40°C dihydro-3-(2-octadecenyl)furan-2,5-dione		Inhalation			
	DNEL	Long term Inhalation	1.2 mg/m³	General population	Local
	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m³	Workers	Local
	DNEL	Long term Oral	1.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	21.16 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	3 mg/kg bw/day	Workers	Systemic

PNECs

Product/substance	Compartment Detail	Value	Method Detail
Distillates (petroleum), hydrotreated heavy paraffinic	Secondary Poisoning	9.33 mg/kg	-
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Secondary Poisoning	9.33 mg/kg	-
dihydro-3-(2-octadecenyl)furan-2,5-dione	Fresh water sediment	340 mg/kg	-
	Marine water sediment	34 mg/kg	-
	Soil	40 mg/kg	-
	Sewage Treatment Plant	8 mg/l	-
	Fresh water	10 µg/l	-
	Marine water	1 µg/l	-

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. EN 166

Skin protection

SECTION 8: Exposure controls/personal protection

- Hand protection** : ☒ Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Hydrocarbon-proof gloves
nitrile rubber
Fluorinated rubber
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
In case of prolonged contact with the product, it is recommended to wear gloves complying with ISO 21420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency
- Body protection** : ☒ Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : ☒ Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : ☒ Ensure adequate ventilation and check that a safe, breathable atmosphere is present before entry into confined spaces. In case of inadequate ventilation wear respiratory protection: Type A/P1. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.
- Environmental exposure controls** : ☒ Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid. [Clear]
- Colour** : Clear.
- Odour** : Characteristic.
- Odour threshold** : Not available.
- Melting point/freezing point** : ☒ Not applicable.
- Initial boiling point and boiling range** : ☒ 316°C (>600.8°F) [ISO 3405]
- Flammability (solid, gas)** : ☒ Not applicable.

SECTION 9: Physical and chemical properties

Upper/lower flammability or explosive limits	: Lower: 0.9% Upper: 7%
Flash point	: Open cup: 210°C (410°F) [Cleveland Open Cup (COC)]
Auto-ignition temperature	: 210°C (>410°F) [ASTM E 659]
Decomposition temperature	: Not applicable.
pH	: Not applicable. Product is non-soluble (in water).
Viscosity	: Kinematic (40°C): 47.4 mm ² /s [ISO 3104]
Solubility(ies)	:

Media	Result
water	Not soluble

Miscible with water	: No.
Partition coefficient: n-octanol/ water	: Not applicable.
Vapour pressure	: 0.013 kPa (<0.1 mm Hg) [room temperature] Not applicable. [50°C (122°F)]
Relative density	: 0.847 [ISO 12185]
Density	: 0.847 g/cm ³ [15°C (59°F)] [ISO 12185]
Vapour density	: 2 [Air = 1]
Particle characteristics	
Median particle size	: Not applicable.

9.2 Other information

No other relevant physical and chemical parameters for the safe use of the product

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
10.5 Incompatible materials	: Strong oxidising agents
10.6 Hazardous decomposition products	: carbon monoxide carbon dioxide nitrogen oxides sulfur oxides Hydrogen sulfide Mercaptans Zinc oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	Result	Species	Dose	Exposure	Test
Distillates (petroleum), hydrotreated heavy paraffinic	LC50 Inhalation Dusts and mists	Rat - Male, Female	>5 mg/l	4 hours	OECD 403 Read across
	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-	OECD 402 Read across
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-	OECD 401 Read across
Distillates (petroleum), solvent-dewaxed heavy paraffinic	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 420
Distillates (petroleum), solvent-dewaxed light paraffinic	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 401
Distillates (petroleum), hydrotreated light paraffinic	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 420
Distillates (petroleum), solvent-refined light paraffinic	LC50 Inhalation Dusts and mists	Rat	5.1 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 420
dihydro-3-(2-octadecenyl) furan-2,5-dione	LD50 Dermal	Rat	>2000 mg/kg	-	402
	LD50 Oral	Rat	>2000 mg/kg	-	425
	LD50 Oral	Rat	>2000 mg/kg	-	425

Conclusion/Summary : Based on available data, the classification criteria are not met.

Acute toxicity estimates

Product/substance	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
OTHER LUBRICANT BASE OILS IP 346 < 3% w/w; Viscosity ≤ 20.5 mm ² /s at 40°C	N/A	N/A	N/A	N/A	5.1

Irritation/Corrosion

Conclusion/Summary

- Skin** : Based on available data, the classification criteria are not met.
- Eyes** : Based on available data, the classification criteria are not met.
- Respiratory** : Based on available data, the classification criteria are not met.

Sensitisation

Conclusion/Summary

- Skin** : Based on available data, the classification criteria are met.
- Respiratory** : Based on available data, the classification criteria are not met.

Mutagenicity

SECTION 11: Toxicological information

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Not available.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Aspiration hazard

Product/substance	Result
<input checked="" type="checkbox"/> Distillates (petroleum), hydrotreated heavy paraffinic Distillates (petroleum), solvent-dewaxed heavy paraffinic Distillates (petroleum), solvent-dewaxed light paraffinic Distillates (petroleum), hydrotreated light paraffinic OTHER LUBRICANT BASE OILS IP 346 < 3% w/w; Viscosity ≤ 20.5 mm²/s at 40°C	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Conclusion/Summary : Based on available data, the classification criteria are not met.

Information on likely routes of exposure : Not available.

Potential acute health effects

Eye contact : ☒ No known significant effects or critical hazards.

Inhalation : ☒ No known significant effects or critical hazards.

Skin contact : ☒ Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.

Ingestion : ☒ No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : ☒ No specific data.

Inhalation : ☒ No specific data.

Skin contact : ☒ Adverse symptoms may include the following:
irritation
redness
dryness
cracking

Ingestion : ☒ No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

SECTION 11: Toxicological information

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : ☒ Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : ☒ During use in engines, contamination of oil with low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.

Mutagenicity : ☒ No known significant effects or critical hazards.

Reproductive toxicity : ☒ No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

11.2.2 Other information

SECTION 12: Ecological information

12.1 Toxicity

Product/substance	Result	Species	Exposure	Test
<input checked="" type="checkbox"/> Distillates (petroleum), hydrotreated heavy paraffinic	Acute EC50 >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
	Acute EC50 >10000 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 202
	Chronic NOEL >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Chronic NOEL >1000 mg/l	Crustaceans - Daphnia magna	21 days	-
	Acute EL50 >10000 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 202
	Acute LL50 >1000 mg/l	Fish - Oncorhynchus mykiss	96 hours	OECD 203
Distillates (petroleum),	Chronic NOEL >1000 mg/l	Crustaceans - Daphnia magna	21 days	OECD 211
	Acute EL50 >100 mg/l	Algae -	72 hours	OECD 201

SECTION 12: Ecological information

solvent-dewaxed light paraffinic	Acute EL50 10000 mg/l	Pseudokirchneriella subcapitata	48 hours	OECD 202
	Acute EL50 ≥100 mg/l	Crustaceans - Daphnia magna	96 hours	OECD 203
	Chronic NOEL >100 mg/l	Fish - Pimephales promelas	72 hours	OECD 201
	Chronic NOEL >1000 mg/l	Algae - Pseudokirchneriella subcapitata	21 days	OECD 211
Distillates (petroleum), hydrotreated light paraffinic	Acute EC50 >100 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 201
	Acute EC50 >10000 mg/l	Algae - Pseudokirchnerella subcapitata	48 hours	OECD 202
	Chronic NOEL 10 mg/l	Daphnia - Daphnia magna	21 days	OECD 211
	Chronic NOEL >1000 mg/l	Daphnia - Daphnia magna	21 days	-
Distillates (petroleum), solvent-refined light paraffinic	Acute EC50 >100 mg/l	Fish - Oncorhynchus mykiss	48 hours	OECD 201
	Acute EC50 >10000 mg/l	Algae - Pseudokirchnerella subcapitata	48 hours	OECD 202
	Chronic NOEL 10 mg/l	Daphnia - Daphnia Magna	21 days	OECD 211
	Chronic NOEL >1000 mg/l	Daphnia - Daphnia Magna	21 days	-
dihydro-3-(2-octadecenyl) furan-2,5-dione	Acute LC50 >10 mg/l	Fish - Oncorhynchus mykiss	96 hours	OECD 203
	Chronic NOEC ≥10 mg/l	Fish - Leuciscus idus	96 hours	OECD 203

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Product/substance	Test	Result	Dose	Inoculum
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
Distillates (petroleum), solvent-dewaxed heavy paraffinic	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
Distillates (petroleum), solvent-dewaxed light paraffinic	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge

Conclusion/Summary : Not available.

Product/substance	Aquatic half-life	Photolysis	Biodegradability
Distillates (petroleum), hydrotreated heavy paraffinic	-	-	Not readily
Distillates (petroleum), solvent-dewaxed heavy paraffinic	-	-	Not readily
Distillates (petroleum), solvent-dewaxed light paraffinic	-	-	Not readily
dihydro-3-(2-octadecenyl) furan-2,5-dione	-	-	Readily

SECTION 12: Ecological information

12.3 Bioaccumulative potential

Product/substance	LogP _{ow}	BCF	Potential
Distillates (petroleum), hydrotreated heavy paraffinic	>4	-	high
Distillates (petroleum), solvent-dewaxed heavy paraffinic	9.2	260	low
Distillates (petroleum), solvent-dewaxed light paraffinic	3.1	-	low
dihydro-3-(2-octadecenyl) furan-2,5-dione	9.36	-	high

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

Mobility in soil : Given its physical and chemical characteristics, the product generally shows low soil mobility. The product is insoluble and floats on water. Loss by evaporation is limited.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

12.7 Other adverse effects

☒ No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : ☒ The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : ☒ Yes.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions: 13 02 05*

SECTION 13: Disposal considerations

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ICAO/IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture UK (GB) /REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

Prior Informed Consent (PIC)

SECTION 15: Regulatory information

Not listed.

Persistent Organic Pollutants

Not listed.

Annex XVII - Restrictions : Not applicable.
on the manufacture,
placing on the market
and use of certain
dangerous substances,
mixtures and articles

Seveso Directive

☒ This product is not controlled under the Seveso Directive.

EU regulations

Industrial emissions : Not listed
(integrated pollution
prevention and control) -
Air

Industrial emissions : Not listed
(integrated pollution
prevention and control) -
Water

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia inventory (AIIC)	: All components are listed or exempted.
Canada inventory	: All components are listed or exempted.
China inventory (IECSC)	: All components are listed or exempted.
Europe inventory	: <input checked="" type="checkbox"/> All components are listed or exempted.
Japan inventory	: Japan inventory (CSCL) : All components are listed or exempted. Japan inventory (ISHL) : Not determined.
New Zealand Inventory of Chemicals (NZIoC)	: All components are listed or exempted.
Philippines inventory (PICCS)	: All components are listed or exempted.
Korea inventory (KECI)	: All components are listed or exempted.

SECTION 15: Regulatory information

Taiwan Chemical Substances Inventory (TCSI)	: All components are listed or exempted.
Thailand inventory	: Not determined.
Turkey inventory	: Not determined.
United States inventory (TSCA 8b)	: All components are listed or exempted.
Vietnam inventory	: Not determined.

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

15.2 Chemical safety assessment	: This product contains substances for which Chemical Safety Assessments are still required.
--	--

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level DMEL = Derived Minimal Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic vPvB = Very Persistent and Very Bioaccumulative PNEC = Predicted No Effect Concentration LC50 = Median lethal concentration LD50 = Median lethal dose OEL = Occupational Exposure Limit VOC = Volatile Organic Compound UVCB Substance of unknown or Variable composition, Complex reaction products or Biological material NOEC No Observed Effect Concentration QSAR = Quantitative Structure–Activity Relationship
-----------------------------------	--

Procedure used to derive the classification

Classification	Justification
Skin Sens. 1, H317	Calculation method

Full text of abbreviated H statements

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

Full text of classifications

Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A

Date of printing : 2022/10/20



TotalEnergies

QUARTZ 9000 FUTURE GF6 0W-20

SDS no. 091127
:

SECTION 16: Other information

Date of issue/ Date of revision : 2022/10/20

Date of previous issue : 2021/08/04

Version : 3

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition : Mixture
Code : 091127
Product name : QUARTZ 9000 FUTURE GF6 0W-20

Section 1 - Title

Short title of the exposure scenario : Formulation additives, lubricants and greases - Industrial

List of use descriptors : **Identified use name:** Formulation additives, lubricants and greases - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15
Sector of end use: SU03, SU10
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02

Environmental contributing scenarios :

Health Contributing scenarios : **General measures applicable to all activities**
General exposures Use in contained systems Elevated temperature - PROC02
Mixing operations Closed systems Batch processes at elevated temperatures - PROC03
Mixing operations Open systems Batch processes at elevated temperatures - PROC04, PROC05
Mixing operations (open systems) - PROC04, PROC05
Process sampling - PROC04, PROC08b
Bulk transfers Dedicated facility - PROC08b
Drum/batch transfers Dedicated facility - PROC08b
Drum/batch transfers Non-dedicated facility - PROC08a
Equipment cleaning and maintenance - PROC08a, PROC08b
Drum and small package filling - PROC09
Laboratory activities - PROC15
Storage - PROC01, PROC02

Processes and activities covered by the exposure scenario	: Industrial formulation of lubricant additives, lubricants and greases. Includes material transfers, mixing, large and small scale packing, sampling, maintenance.
--	---

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

No exposure scenario required

Contributing scenario controlling worker exposure for 2: General measures applicable to all activities

Concentration of substance in mixture or article : Covers percentage substance in the product up to 100 %. (unless stated differently)

Physical state : Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

Amounts used : Not applicable.

Frequency and duration of use/exposure : Covers daily exposures up to 8 hours (unless stated differently)

Human factors not influenced by risk management : Not applicable.

Other conditions affecting workers exposure : Covers percentage substance in the product up to 100% (unless stated differently)

Date of issue/Date of revision : 11/26/2020

20/31

Conditions and measures related to personal protection, hygiene and health evaluation

Advice on general occupational hygiene : Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Avoid direct eye contact with product, also via contamination on hands.

Personal protection : Use suitable eye protection.

Contributing scenario controlling worker exposure for 3: General exposures Use in contained systems Elevated temperature

No other specific measures identified.

Conditions and measures related to personal protection, hygiene and health evaluation**Contributing scenario controlling worker exposure for 4: Mixing operations Closed systems Batch processes at elevated temperatures**

Ventilation control measures : Provide extract ventilation to points where emissions occur.

Conditions and measures related to personal protection, hygiene and health evaluation**Contributing scenario controlling worker exposure for 5: Mixing operations Open systems Batch processes at elevated temperatures**

Frequency and duration of use/exposure : Avoid carrying out activities involving exposure for more than 4 hours per day.

Ventilation control measures : Provide extract ventilation to points where emissions occur.

Conditions and measures related to personal protection, hygiene and health evaluation**Contributing scenario controlling worker exposure for 6: Mixing operations (open systems)**

Ventilation control measures : Provide extract ventilation to points where emissions occur.

Conditions and measures related to personal protection, hygiene and health evaluation**Contributing scenario controlling worker exposure for 7: Process sampling**

Frequency and duration of use/exposure : Avoid carrying out activities involving exposure for more than 1 hour per day.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection : Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Contributing scenario controlling worker exposure for 8: Bulk transfers Dedicated facility

Frequency and duration of use/exposure : Avoid carrying out activities involving exposure for more than 4 hours per day.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection : Wear chemical-resistant gloves (tested to EN374) in combination with intensive management supervision controls.

Contributing scenario controlling worker exposure for 9: Drum/batch transfers Dedicated facility

Ventilation control measures : Provide extract ventilation to points where emissions occur.

Conditions and measures related to personal protection, hygiene and health evaluation

Contributing scenario controlling worker exposure for 10: Drum/batch transfers Non-dedicated facility

Frequency and duration of use/exposure : Avoid carrying out activities involving exposure for more than 1 hour per day.

Ventilation control measures : Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection : Wear chemical-resistant gloves (tested to EN374) in combination with intensive management supervision controls.

Contributing scenario controlling worker exposure for 11: Equipment cleaning and maintenance

Technical conditions and measures to control dispersion from source towards the worker : Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Engineering controls : Drain down and flush system prior to equipment break-in or maintenance.

Conditions and measures related to personal protection, hygiene and health evaluation

Advice on general occupational hygiene : Clear spills immediately.

Personal protection : Wear chemical-resistant gloves (tested to EN374) in combination with intensive management supervision controls.

Contributing scenario controlling worker exposure for 12: Drum and small package filling

Ventilation control measures : Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection : Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Contributing scenario controlling worker exposure for 13: Laboratory activities

Frequency and duration of use/exposure : Avoid carrying out activities involving exposure for more than 4 hours per day.

Conditions and measures related to personal protection, hygiene and health evaluation**Contributing scenario controlling worker exposure for 14: Storage**

Engineering controls : Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation**Section 3 - Exposure estimation and reference to its source**

Website: : Not applicable.

Exposure estimation and reference to its source - Environment: 1:

Exposure assessment (environment): : Used ECETOC TRA model.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 2: General measures applicable to all activities

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 3: General exposures Use in contained systems Elevated temperature

- Exposure assessment (human):** : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 4: Mixing operations Closed systems Batch processes at elevated temperatures

- Exposure assessment (human):** : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 5: Mixing operations Open systems Batch processes at elevated temperatures

- Exposure assessment (human):** : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 6: Mixing operations (open systems)

- Exposure assessment (human):** : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 7: Process sampling

- Exposure assessment (human):** : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 8: Bulk transfers Dedicated facility

- Exposure assessment (human):** : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 9: Drum/batch transfers Dedicated facility

- Exposure assessment (human):** : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 10: Drum/batch transfers Non-dedicated facility

- Exposure assessment (human):** : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 11: Equipment cleaning and maintenance

Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Exposure estimation and reference to its source - Workers: 12: Drum and small package filling

Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Exposure estimation and reference to its source - Workers: 13: Laboratory activities

Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Exposure estimation and reference to its source - Workers: 14: Storage

Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction .
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction .

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition : Mixture
Code : 091127
Product name : QUARTZ 9000 FUTURE GF6 0W-20

Section 1 - Title

Short title of the exposure scenario : General use of lubricants and greases in vehicles or machinery - Industrial

List of use descriptors : **Identified use name:** General use of lubricants and greases in vehicles or machinery - Industrial
Process Category: PROC01, PROC02, PROC08b, PROC09
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC04, ERC07

Environmental contributing scenarios :

Health Contributing scenarios : **General measures applicable to all activities**
General exposures (closed systems) - PROC01
Initial factory fill of equipment Use in contained systems - PROC02, PROC09
Initial factory fill of equipment Open systems - PROC08b
Operation of equipment containing engine oils and similar Use in contained systems - PROC01
Equipment cleaning and maintenance - PROC08b
Equipment cleaning and maintenance Operation is carried out at elevated temperature (> 20°C above ambient temperature) - PROC08b
Storage - PROC01, PROC02

Processes and activities covered by the exposure scenario	: Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.
--	---

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

No exposure scenario required

Contributing scenario controlling worker exposure for 2: General measures applicable to all activities

Concentration of substance in mixture or article : Covers percentage substance in the product up to 100% (unless stated differently).

Physical state : Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure.

Frequency and duration of use/exposure : Covers daily exposures up to 8 hours (unless stated differently).

Other conditions affecting workers exposure : Assumes use at not more than 20°C above ambient temperature. unless stated differently.
Assumes a good basic standard of occupational hygiene has been implemented.

Conditions and measures related to personal protection, hygiene and health evaluation

Advice on general occupational hygiene : Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Avoid direct eye contact with product, also via contamination on hands.

Personal protection : Use suitable eye protection.

Contributing scenario controlling worker exposure for 3: General exposures (closed systems)

No other specific measures identified.

Conditions and measures related to personal protection, hygiene and health evaluation**Contributing scenario controlling worker exposure for 4: Initial factory fill of equipment Use in contained systems**

No other specific measures identified.

Conditions and measures related to personal protection, hygiene and health evaluation**Contributing scenario controlling worker exposure for 5: Initial factory fill of equipment Open systems****Frequency and duration of use/exposure** : Avoid carrying out activities involving exposure for more than 4 hours per day.**Ventilation control measures** : Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour)**Conditions and measures related to personal protection, hygiene and health evaluation****Contributing scenario controlling worker exposure for 6: Operation of equipment containing engine oils and similar Use in contained systems**

No other specific measures identified.

Conditions and measures related to personal protection, hygiene and health evaluation**Contributing scenario controlling worker exposure for 7: Equipment cleaning and maintenance****Technical conditions and measures at process level (source) to prevent release** : Retain drain-downs in sealed storage pending disposal or for subsequent recycle.**Engineering controls** : Drain down system prior to equipment break-in or maintenance.**Ventilation control measures** : Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).**Conditions and measures related to personal protection, hygiene and health evaluation****Personal protection** : Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.**Contributing scenario controlling worker exposure for 8: Equipment cleaning and maintenance Operation is carried out at elevated temperature (> 20°C above ambient temperature)****Technical conditions and measures to control dispersion from source towards the worker** : Retain drain-downs in sealed storage pending disposal or for subsequent recycle.**Engineering controls** : Drain down system prior to equipment break-in or maintenance.**Ventilation control measures** : Provide extract ventilation to emission points when contact with warm (>50°C) lubricant is likely.**Conditions and measures related to personal protection, hygiene and health evaluation****Personal protection** : Wear chemical-resistant gloves (tested to EN374) in combination with intensive management supervision controls.**Contributing scenario controlling worker exposure for 9: Storage****Engineering controls** : Store substance within a closed system.**Conditions and measures related to personal protection, hygiene and health evaluation****Section 3 - Exposure estimation and reference to its source****Website:** : Not applicable.**Exposure estimation and reference to its source - Environment: 1:****Exposure assessment (environment):** : Used ECETOC TRA model.**Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 2: General measures applicable to all activities

- Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 3: General exposures (closed systems)

- Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 4: Initial factory fill of equipment Use in contained systems

- Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 5: Initial factory fill of equipment Open systems

- Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 6: Operation of equipment containing engine oils and similar Use in contained systems

- Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 7: Equipment cleaning and maintenance

- Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 8: Equipment cleaning and maintenance Operation is carried out at elevated temperature (> 20°C above ambient temperature)

- Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 9: Storage

- Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction .
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction .

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.

Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the substance or mixture

Product definition : Mixture
Code : 091127
Product name : QUARTZ 9000 FUTURE GF6 0W-20

Section 1 - Title

Short title of the exposure scenario : General use of lubricants and greases in vehicles or machinery - Professional

List of use descriptors : **Identified use name:** General use of lubricants and greases in vehicles or machinery - Professional
Process Category: PROC01, PROC02, PROC08a, PROC08b, PROC20
Sector of end use: SU22
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC09a, ERC09b

Environmental contributing scenarios :

Health Contributing scenarios : **General measures applicable to all activities**
Operation of equipment containing engine oils and similar Use in contained systems - PROC01
Material transfers Non-dedicated facility - PROC08a
Equipment cleaning and maintenance Dedicated facility - PROC08b, PROC20
Storage - PROC01, PROC02

Processes and activities covered by the exposure scenario : Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

No exposure scenario required

Contributing scenario controlling worker exposure for 2: General measures applicable to all activities

Concentration of substance in mixture or article : Covers percentage substance in the product up to 100% (unless stated differently).

Physical state : Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure.

Frequency and duration of use/exposure : Covers daily exposures up to 8 hours (unless stated differently).

Other conditions affecting workers exposure : Assumes use at not more than 20°C above ambient temperature. unless stated differently.
Assumes a good basic standard of occupational hygiene has been implemented.

Conditions and measures related to personal protection, hygiene and health evaluation

Advice on general occupational hygiene : Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Avoid direct eye contact with product, also via contamination on hands.

Personal protection : Use suitable eye protection.

Contributing scenario controlling worker exposure for 3: Operation of equipment containing engine oils and similar Use in contained systems

No other specific measures identified.

Conditions and measures related to personal protection, hygiene and health evaluation**Contributing scenario controlling worker exposure for 4: Material transfers Non-dedicated facility****Frequency and duration of use/exposure** : Avoid carrying out activities involving exposure for more than 4 hours per day.**Conditions and measures related to personal protection, hygiene and health evaluation****Personal protection** : Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.**Contributing scenario controlling worker exposure for 5: Equipment cleaning and maintenance Dedicated facility****Technical conditions and measures at process level (source) to prevent release** : Retain drain-downs in sealed storage pending disposal or for subsequent recycle.**Engineering controls** : Drain down system prior to equipment break-in or maintenance.**Conditions and measures related to personal protection, hygiene and health evaluation****Contributing scenario controlling worker exposure for 6: Storage****Engineering controls** : Store substance within a closed system.**Conditions and measures related to personal protection, hygiene and health evaluation****Section 3 - Exposure estimation and reference to its source****Website:** : Not applicable.**Exposure estimation and reference to its source - Environment: 1:****Exposure assessment (environment):** : Used ECETOC TRA model.**Exposure estimation and reference to its source** : Not available.**Exposure estimation and reference to its source - Workers: 2: General measures applicable to all activities****Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.**Exposure estimation and reference to its source** : Not available.**Exposure estimation and reference to its source - Workers: 3: Operation of equipment containing engine oils and similar Use in contained systems****Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.**Exposure estimation and reference to its source** : Not available.**Exposure estimation and reference to its source - Workers: 4: Material transfers Non-dedicated facility****Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.**Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 5: Equipment cleaning and maintenance Dedicated facility

- Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 6: Storage

- Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

- Environment** : Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction.
- Health** : Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction.

Additional good practice advice beyond the REACH CSA

- Environment** : Not available.
- Health** : Not available.