according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL GREY AUTOMATIC SILICONE GASKET MAKER 260°C

Creation date 12th May 2021
Revision date 14th March 2025 Version

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier MA PROFESSIONAL GREY AUTOMATIC SILICONE GASKET

MAKER 260°C

3.0

Substance / mixture mixture M-31012022

UFI TCJ0-E069-200M-FXNY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Mixture's intended use Barrier (Sealant).

Main intended use

PC-ADH-OTH Other adhesives and sealants

Mixture uses advised against

The product should not be used in ways other than those referred in Section 1.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Name or trade name AMTRA Sp. z o. o.

Address Schonów 3, Sosnowiec, 41-200

Poland

VAT Reg No PL6250009241
Phone +48 32 294 41 00
E-mail amtra@amtra.pl

Competent person responsible for the safety data sheet

Name AMTRA Sp. z o. o. E-mail amtra@amtra.pl

1.4. Emergency telephone number

European emergency number: 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Aerosol 3, H229 Aquatic Chronic 3, H412

Most serious adverse physico-chemical effects

Pressurised container: May burst if heated.

Most serious adverse effects on human health and the environment

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Signal word

Warning

Hazard statements

H229 Pressurised container: May burst if heated.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P251 Do not pierce or burn, even after use. P273 Avoid release to the environment.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C.

P501 Dispose of contents/container to by disposing in a hazardous waste receptacle.

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL GREY AUTOMATIC SILICONE GASKET MAKER 260°C

Creation date 12th May 2021

Revision date 14th March 2025 Version 3.0

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
CAS: 17865-07-5 EC: 241-816-9 Registration number: 01-2119966899-07- xxxx	Propyltriacetoxysilan	1-<2.5	Skin Corr. 1B, H314 EUH071	
CAS: 13463-67-7 EC: 643-044-1	Titanium dioxide	0.1-<1	not classified as dangerous	
Index: 014-018-00-1 CAS: 556-67-2 EC: 209-136-7	octamethylcyclotetrasiloxane	0.01-<0.1	Flam. Liq. 3, H226 Repr. 2 (***), H361f Aquatic Chronic 1, H410 (M=10)	1, 2, 3

Notes

- *** reproductive toxicity: supplementary letters specify whether fetal harm (d) or fertility harm (f) may occur
- Substance of very high concern SVHC. 1
- Persistent, bioaccumulative and toxic or very persistent and very bioaccumulative
- The use of the substance is restricted by Annex XVII of REACH Regulation

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

Description of first aid measures 4.1.

If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible.

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes.

If swallowed

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Not expected.

If on skin

Not expected.

If in eyes

When intruding eyes, it can evoke irritation.

If swallowed

Not expected.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL GREY AUTOMATIC SILICONE GASKET MAKER 260°C

Creation date 12th May 2021

Revision date 14th March 2025 Version 3.0

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Pressurised container: May burst if heated. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale aerosols.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Do not inhale aerosols. No smoking. Protect against direct sunlight. Do not pierce or burn, even after use. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Avoid release to the environment.

7.2. Conditions for safe storage, including any incompatibilities

Recommended storage temperature is from +5 °C to +30 °C. Protect against frost. Protect from sunlight. Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to temperatures exceeding 50 °C.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains no substances for which occupational exposure limits are set.

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL GREY AUTOMATIC SILICONE GASKET MAKER 260°C

Creation date 12th May 2021
Revision date 14th March 2025 Version 3.0

8.2. Exposure controls

Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

It is not needed.

Skin protection

Hand protection:

Chemical resistant gloves should be worn whenever working with chemical products when a risk assessment indicates this is necessary.

The selected protective gloves must meet the requirements of the EN 374-1 standard. Recommended for long-term contact:

Material for protective gloves: nitrile rubber. Thickness: 0.11 mm

Breakthrough time: > 480 min.

Efficiency class: 6

Recommended for momentary contact: Material for protective gloves: nitrile rubber

Thickness: 0.11 mm

Breakthrough time: > 480 min.

Efficiency class: 6

Hand protection: Protective gloves resistant to the product. Contaminated skin should be washed thoroughly.

Respiratory protection

Respirator.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state liquid Colour grey

Odour characteristic Melting point/freezing point not determined Boiling point or initial boiling point and boiling range not determined Flammability non-inflammable Lower and upper explosion limit not determined Flash point >162 °C Auto-ignition temperature 365-470 °C Decomposition temperature not determined

pH non-soluble (in water)
Kinematic viscosity >21 mm²/s at 40 °C

Solubility in water insoluble

Partition coefficient n-octanol/water (log value) not determined

Vapour pressure not determined

Density and/or relative density not determined

Relative vapour density not determined

9.2. Other information

none

SECTION 10: Stability and reactivity

Particle characteristics

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

not determined

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL GREY AUTOMATIC SILICONE GASKET MAKER 260°C

Creation date 12th May 2021
Revision date 14th March 2025 Version 3.0

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost. Pressurised container: May burst if heated.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

Acute toxicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Skin corrosion/irritation

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Serious eye damage/irritation

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Respiratory or skin sensitisation

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Germ cell mutagenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Carcinogenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Reproductive toxicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Toxicity for specific target organ - single exposure

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Toxicity for specific target organ - repeated exposure

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Aspiration hazard

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL GREY AUTOMATIC SILICONE GASKET MAKER 260°C

Creation date 12th May 2021
Revision date 14th March 2025 Version

11.2. Information on other hazards

Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption for humans.

3.0

Other information

not available

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects. Data for the components of the mixture are not available.

12.2. Persistence and degradability

No data are available for either the mixture or the components.

12.3. Bioaccumulative potential

No data are available for either the mixture or the components.

12.4. Mobility in soil

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PMT or vPvM components.

12.5. Results of PBT and vPvB assessment

Based on the available data, the criteria for classification of the mixture are not met.

12.6. Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption in the environment.

12.7. Other adverse effects

Data not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2 Gases

14.4. Packing group

not relevant

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL GREY AUTOMATIC SILICONE GASKET MAKER 260°C

3.0

Creation date 12th May 2021
Revision date 14th March 2025 Version

Additional information

Hazard identification No.

UN number Classification code Safety signs 1950

5A 2.2



Road transport - ADR

Special provisions 190, 327, 344, 625

Limited quantities 1 L Excepted quantities E0

Packaging

Packing instructions P207, LP200 Special packing provisions PP87, RR6, L2

Mixed packing provisionsMP9Transport category3Tunnel restriction code(E)

Special provision for

packages V14

loading, unloading and handling CV9, CV12

Railway transport - RID

Special provisions 190, 327, 625

Excepted quantities E0

Packaging

Packing instructions LP02, P003

Special packing provisions L2, PP17, PP87, RR6

Mixed packing provisions MP9
Transport category 3

Special provision for

packages W14 loading, unloading and handling CW12, CW9

Marine transport - IMDG

EmS (emergency plan) F-D, S-U MFAG 620

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended

octamethy l cyclotetras i loxane

oddinion, i of diototi dello kano		
Restriction	Conditions of restriction	
70	1. Shall not be placed on the market (a) as a substance on its own;	

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL GREY AUTOMATIC SILICONE GASKET MAKER 260°C

Creation date 12th May 2021
Revision date 14th March 2025

Revision date 14th March 2025 Version 3.0

octame thy l cyclotetra siloxane

Restriction	Conditions of restriction
Restriction	(b) as a constituent of other substances; or
	(c) in mixtures;
	in a concentration equal to or greater than 0,1 % by weight of the respective substance after 6 June
	2026.
	2. Shall not be used as a solvent for the dry cleaning of textiles, leather and fur after 6 June 2026.
	3. By way of derogation:
	(a) for D4 and D5 in wash-off cosmetic products, paragraph 1, point (c), shall apply after 31 January
	2020.
	For the purposes of this point, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1), point (a), of Regulation (EC) No 1223/2009 of the European Parliament and of the Council that, under normal conditions of use, are washed off with water after application; (b) for all cosmetic products other than the ones mentioned in paragraph 3(a), paragraph 1 shall apply after 6 June 2027;
	(c) for devices as defined in Article 1(4) of Regulation (EU) 2017/745 of the European Parliament and of the Council and in Article 1(2) of Regulation (EU) 2017/746 of the European Parliament and the Council, paragraph 1 shall apply after 6 June 2031;
	(d) for medicinal products, as defined in Article 1, point 2, of Directive 2001/83/EC, and for veterinary medicinal products, as defined in Article 4(1) of Regulation (EU) 2019/6, paragraph 1 shall apply after 6 June 2031;
	(e) for D5 as a solvent in the dry cleaning of textiles, leather and fur, paragraphs 1 and 2 shall apply after 6 June 2034.
	4. By way of derogation, paragraph 1 shall not apply to the:
	(a) placing on the market of D4, D5 and D6 for the following industrial uses:
	— as a monomer in the production of silicone polymer,
	— as an intermediate in the production of other silicon substances,
	— as a monomer in polymerisation,
	— in the formulation or (re)packing of mixtures,
	in the production of articles,in non-metal surface treatment;
	(b) placing on the market of D5 and D6 for use as devices, as defined in Article 1(4) of Regulation (EU) 2017/745, for the treatment and care of scars and wounds, the prevention of wounds and the care of stoma;
	(c) placing on the market of D5 for professional use in the cleaning or restoration of art and antiques;
	(d) placing on the market of D4, D5 and D6 for use as laboratory reagent in research and development activities carried out under controlled conditions.
	5. By way of derogation, paragraph 1, point (b), shall not apply to the placing on the market of D4, D5 and D6:
	 as a constituent of a silicone polymer on its own, as a constituent of a silicone polymer in a mixture derogated under paragraph 6.
	6. By way of derogation, paragraph 1, point (c), shall not apply to the placing on the market of mixtures that contain D4, D5 or D6 as residues from silicone polymers, under the following conditions:
	(a) D4, D5 or D6 in a concentration equal to or less than 1 % by weight of the respective substance in the mixture, for use in adhesion, sealing, gluing and casting;
	(b) D4 in a concentration equal to or less than 0,5 % by weight, or D5 or D6 in a concentration equal to or less than 0,3 % by weight of either substance in the mixture for use as protective coatings (including marine coatings);
	(c) D4, D5 or D6 in a concentration equal to or less than 0,2 % by weight of the respective substance in the mixture, for use as devices as defined in Article 1(4) of Regulation (EU) 2017/745 and in Article 1(2) of Regulation (EU) 2017/746, other than the devices referred to in paragraph 6(d); (d) D5 in a concentration equal to or less than 0,3 % by weight in the mixture or D6 in a concentration equal to or less than 1 % by weight in the mixture, for use as devices as defined in Article 1(4) of Regulation (EU) 2017/745, for dental impression;
	(e) D4 in a concentration equal to or less than 0,2 % by weight in the mixture, or D5 or D6 in a concentration equal to or less than 1 % by weight of either substance in the mixture for use as

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL GREY AUTOMATIC SILICONE GASKET MAKER 260°C

Creation date 12th May 2021

Revision date 14th March 2025 Version 3.0

octamethylcyclotetrasiloxane

on Conditions of restriction	
silicone insoles for horses, or as horseshoes; (f) D4, D5 or D6 in a concentration equal to or less than 0,5 % by weight of the responsion the mixture, for use as adhesion promoters; (g) D4, D5 or D6 in a concentration equal to or less than 1 % by weight of the responsion the mixture, for use in 3D-printing; (h) D5 in a concentration equal to or less than 1 % by weight in the mixture or D6 in equal to or less than 3 % by weight in the mixture, for rapid prototyping and mould performance uses stabilised by quartz filler; (i) D5 or D6 in a concentration equal to or less than 1 % by weight of either substant mixture, for use in pad printing, or manufacturing of printing pads; (j) D6 in a concentration equal to or less than 1 % by weight of the mixture, for prothe cleaning or restoration of art and antiques. 7. By way of derogation, paragraphs 1 and 2 shall not apply to the placing on the mixture.	ective substance in a concentration making, or high ace in the fessional use in
(j) D6 in a concentration equal to or less than 1 % by weight of the mixture, for protein the cleaning or restoration of art and antiques.	arket

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

EUH071	•	Corrosive to the respiratory tract.
H226		Flammable liquid and vapour.

H229 Pressurised container: May burst if heated.
H314 Causes severe skin burns and eye damage.

H361f Suspected of damaging fertility.

H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P251 Do not pierce or burn, even after use.
P273 Avoid release to the environment.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C.

P501 Dispose of contents/container to by disposing in a hazardous waste receptacle.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR European agreement concerning the international carriage of dangerous goods by

road

Aerosol Aerosol

Aquatic Chronic Hazardous to the aquatic environment (chronic)

BCF Bioconcentration Factor
CAS Chemical Abstracts Service

CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of

substance and mixtures

EC Identification code for each substance listed in EINECS

EINECS European Inventory of Existing Commercial Chemical Substances

EmS Emergency plan EU European Union

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL GREY AUTOMATIC SILICONE GASKET MAKER 260°C

Creation date 12th May 2021
Revision date 14th March 2025 Version 3.0

EuPCS European Product Categorisation System

Flam. Lig. Flammable liquid

IATA International Air Transport Association

IBC International Code For The Construction And Equipment of Ships Carrying

Dangerous Chemicals

ICAO International Civil Aviation Organization
IMDG International Maritime Dangerous Goods
IMO International Maritime Organization

INCI International Nomenclature of Cosmetic Ingredients
ISO International Organization for Standardization
IUPAC International Union of Pure and Applied Chemistry

 log Kow
 Octanol-water partition coefficient

 OEL
 Occupational Exposure Limits

 PBT
 Persistent, bioaccumulative and toxic

PMT Persistent, mobile and toxic

ppm Parts per million

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

Repr. Reproductive toxicity

RID Agreement on the transport of dangerous goods by rail

Skin Corr. Skin corrosion

UN Four-figure identification number of the substance or article taken from the UN

Model Regulations

UVCB Substances of unknown or variable composition, complex reaction products or

biological materials

VOC Volatile organic compounds

vPvB Very persistent and very bioaccumulative

vPvM Very persistent and very mobile

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 3.0 replaces the SDS version from Monday, 31 January 2022. Changes were made in sections 1, 2, 11, 12, 13, 15 and 16.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.