

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 16

SDS No.: 357779

Revision: 24.10.2022

printing date: 24.07.2023

Replaces version from: 28.09.2022

TEROSON MS 9120 SF BK

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TEROSON MS 9120 SF BK

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

1-Component sealant

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

2.2. Label elements

Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Supplemental information Contains: Trimethoxyvinylsilane May produce an allergic reaction.

Safety data sheet available on request.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration >= 0.1% and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in concentration ≥ the concentration limit that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. EC Number REACH-Reg No. | Concentration | Classification | Specific Conc. Limits, M- factors and ATEs | Add. Information |
|--|---------------|--|---|---------------------|
| triethyl phosphate 78-40-0 201-114-5 01-2119492852-28 | 5- < 10 % | Eye Irrit. 2, H319 Acute Tox. 4, Oral, H302 | | |
| Trimethoxyvinylsilane 2768-02-7 220-449-8 01-2119513215-52 | 0,1-< 1 % | Flam. Liq. 3, H226 Acute Tox. 4, Inhalation, H332 STOT RE 2, H373 Skin Sens. 1B, H317 | | |
| Bis(2,2,6,6-tetramethyl-4- piperidyl) sebacate 52829-07-9 258-207-9 01-2119537297-32 | 0,1-< 1 % | Repr. 2, H361f Eye Dam. 1, H318 Aquatic Chronic 2, H411 Aquatic Acute 1, H400 | M acute = 1 | |

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing. If necessary, see a dermatologist.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

An allergic reaction cannot be excluded after repeated skin contact.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

Remove mechanically.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Hygiene measures:

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Temperatures between + 5 °C and + 35 °C

Protect from direct sun-light and temperature above 50°C in any case.

Store in a cool, dry place.

7.3. Specific end use(s)

1-Component sealant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|--|-----|-------------------|--------------------------------------|--|-----------------|
| Calcium carbonate 471-34-1 [CALCIUM CARBONATE, INHALABLE DUST] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |
| Calcium carbonate 471-34-1 [CALCIUM CARBONATE, RESPIRABLE DUST] | | 4 | Time Weighted Average (TWA): | | EH40 WEL |
| Calcium carbonate 471-34-1 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE] | | 4 | Time Weighted Average (TWA): | | EH40 WEL |
| Calcium carbonate 471-34-1 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |
| Calcium carbonate 471-34-1 [Dust, inhalable dust] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |
| Calcium carbonate 471-34-1 [Dust, respirable dust] | | 4 | Time Weighted Average (TWA): | | EH40 WEL |
| Carbon black 1333-86-4 [CARBON BLACK] | | 3,5 | Time Weighted Average (TWA): | | EH40 WEL |
| Carbon black 1333-86-4 [CARBON BLACK] | | 7 | Short Term Exposure Limit (STEL): | 15 minutes | EH40 WEL |

Occupational Exposure Limits

Valid for

Ireland

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|------------------------------|--|-----------------|
| Calcium carbonate 471-34-1 [CALCIUM CARBONATE] | | 4 | Time Weighted Average (TWA): | | IR_OEL |
| Calcium carbonate 471-34-1 [CALCIUM CARBONATE] | | 10 | Time Weighted Average (TWA): | | IR_OEL |
| Calcium carbonate 471-34-1 [DUSTS NON-SPECIFIC] | | 4 | Time Weighted Average (TWA): | | IR_OEL |
| Calcium carbonate 471-34-1 [DUSTS NON-SPECIFIC] | | 10 | Time Weighted Average (TWA): | | IR_OEL |
| Carbon black 1333-86-4 [CARBON BLACK] | | 3 | Time Weighted Average (TWA): | | IR_OEL |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|--|------------------------------------|-----------------|-----------------|-----|------------|--------|---------|
| | | F | mg/l | ppm | mg/kg | others | |
| triethyl phosphate 78-40-0 | aqua (freshwater) | | 0,632 mg/l | | | | |
| triethyl phosphate 78-40-0 | aqua (marine water) | | 0,0632 mg/l | | | | |
| triethyl phosphate 78-40-0 | sewage treatment plant (STP) | | 298,5 mg/l | | | | |
| triethyl phosphate 78-40-0 | Soil | | | | 0,64 mg/kg | | |
| triethyl phosphate 78-40-0 | sediment (freshwater) | | | | 5 mg/kg | | |
| triethyl phosphate 78-40-0 | sediment (marine water) | | | | 0,5 mg/kg | | |
| triethyl phosphate 78-40-0 | Freshwater - intermittent | | 9 mg/l | | | | |
| Trimethoxyvinylsilane 2768-02-7 | aqua (freshwater) | | 0,4 mg/l | | | | |
| Trimethoxyvinylsilane 2768-02-7 | aqua (marine water) | | 0,04 mg/l | | | | |
| Trimethoxyvinylsilane 2768-02-7 | Freshwater - intermittent | | 1,21 mg/l | | | | |
| Trimethoxyvinylsilane 2768-02-7 | sediment (freshwater) | | | | 1,5 mg/kg | | |
| Trimethoxyvinylsilane 2768-02-7 | sediment (marine water) | | | | 0,15 mg/kg | | |
| Trimethoxyvinylsilane 2768-02-7 | Soil | | | | 0,06 mg/kg | | |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | aqua (freshwater) | | 0,004 mg/l | | | | |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | aqua (marine water) | | 0,00038 mg/l | | | | |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | Freshwater - intermittent | | 0,007 mg/l | | | | |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | sediment (freshwater) | | | | 5,9 mg/kg | | |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | sediment (marine water) | | | | 0,59 mg/kg | | |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | Soil | | | | 1,18 mg/kg | | |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | sewage treatment plant (STP) | | 1 mg/l | | | | |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|--|-----------------------|----------------------|--|------------------|------------|---------|
| triethyl phosphate 78-40-0 | General population | oral | Acute/short term exposure - systemic effects | | 5 mg/kg | |
| triethyl phosphate 78-40-0 | General population | oral | Long term exposure - systemic effects | | 1 mg/kg | |
| triethyl phosphate 78-40-0 | General population | inhalation | Long term exposure - systemic effects | | 1,74 mg/m3 | |
| triethyl phosphate 78-40-0 | General population | dermal | Long term exposure - systemic effects | | 1 mg/kg | |
| triethyl phosphate 78-40-0 | Workers | dermal | Long term exposure - systemic effects | | 2 mg/kg | |
| triethyl phosphate 78-40-0 | Workers | inhalation | Long term exposure - systemic effects | | 9,9 mg/m3 | |
| Trimethoxyvinylsilane 2768-02-7 | Workers | dermal | Long term exposure - systemic effects | | 0,91 mg/kg | |
| Trimethoxyvinylsilane 2768-02-7 | Workers | inhalation | Long term exposure - systemic effects | | 27,6 mg/m3 | |
| Trimethoxyvinylsilane 2768-02-7 | General population | dermal | Long term exposure - systemic effects | | 0,63 mg/kg | |
| Trimethoxyvinylsilane 2768-02-7 | General population | inhalation | Long term exposure - systemic effects | | 6,8 mg/m3 | |
| Trimethoxyvinylsilane 2768-02-7 | General population | oral | Long term exposure - systemic effects | | 0,63 mg/kg | |
| Trimethoxyvinylsilane 2768-02-7 | Workers | inhalation | Acute/short term exposure - systemic effects | | 73,6 mg/m3 | |
| Trimethoxyvinylsilane 2768-02-7 | General population | inhalation | Acute/short term exposure - systemic effects | | 54,4 mg/m3 | |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | Workers | dermal | Long term exposure - systemic effects | | 1,8 mg/kg | |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | Workers | Inhalation | Long term exposure - systemic effects | | 1,27 mg/m3 | |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | General population | Inhalation | Long term exposure - systemic effects | | 0,31 mg/m3 | |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | General population | dermal | Long term exposure - systemic effects | | 0,9 mg/kg | |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | General population | oral | Long term exposure - systemic effects | | 0,18 mg/kg | |

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

The product should only be used at workplaces with intensive ventilation/extraction.

If intensive ventilation/extraction is not possible respiratory protection equipment with ABEK P2 filter (EN 14387) should be worn.

Hand protection:

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Polychloroprene (CR; >= 1 mm thickness) or natural rubber (NR; >= 1 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Polychloroprene (CR; >= 1 mm thickness) or natural rubber (NR; >= 1 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Protective goggles

Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state solid
Delivery form paste
Colour black
Odor characteristic

Melting point Not applicable, Determination technically not possible

Solidification temperature Not applicable, Product is a solid.

Initial boiling point 303 °C (577.4 °F)

Flammability

Explosive limits

Not applicable, Product is a solid.

Flash point

Not applicable, Product is a solid.

Decomposition temperature Not applicable, Substance/mixture is not self-reactive, no

organic peroxide and does not decompose under foreseen

conditions of use

pH Not applicable, Product reacts with water.

Viscosity (kinematic) Not applicable, Product is a solid.

Viscosity, dynamic 250 Pa*s no method

(; 20 °C (68 °F))

Solubility (qualitative) Reacts with water.

(20 °C (68 °F); Solvent: Water)

Partition coefficient: n-octanol/water Not applicable Mixture

Vapour pressure 9,1 hPa

(20 °C (68 °F))

Density 1,48 g/cm3 no method

(20 °C (68 °F)) Bulk density 1,48 g/cm3

Relative vapour density:

Not applicable, Product is a solid.

Particle characteristics

Not applicable, mixture is a paste.

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

No decomposition if used according to specifications.

SECTION 11: Toxicological information

General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | Value | Value | Species | Method |
|--|-------|-------------|---------|--|
| CAS-No. | type | | | |
| triethyl phosphate 78-40-0 | LD50 | 1.600 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| Trimethoxyvinylsilane 2768-02-7 | LD50 | 7.120 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | LD50 | 3.700 mg/kg | rat | OECD Guideline 423 (Acute Oral toxicity) |

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | Value | Value | Species | Method |
|--|-------|----------------|---------|--|
| CAS-No. | type | | | |
| triethyl phosphate 78-40-0 | LD50 | > 20.000 mg/kg | rabbit | OECD Guideline 402 (Acute Dermal Toxicity) |
| Trimethoxyvinylsilane 2768-02-7 | LD50 | 3.200 mg/kg | rabbit | OECD Guideline 402 (Acute Dermal Toxicity) |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | LD50 | > 3.170 mg/kg | rat | OECD Guideline 402 (Acute Dermal Toxicity) |

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | Value | Value | Test atmosphere | Exposure | Species | Method |
|---------------------------------|-------|--------------|-----------------|----------|---------|--|
| CAS-No. | type | | | time | | |
| triethyl phosphate 78-40-0 | LC50 | > 8,817 mg/l | dust/mist | 4 h | rat | OECD Guideline 403 (Acute Inhalation Toxicity) |
| Trimethoxyvinylsilane 2768-02-7 | LC50 | 16,8 mg/l | vapour | 4 h | rat | OECD Guideline 403 (Acute Inhalation Toxicity) |

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|--|----------------|---------------|---------|--|
| triethyl phosphate 78-40-0 | not irritating | | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| Trimethoxyvinylsilane 2768-02-7 | not irritating | | rabbit | other guideline: |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | not irritating | 24 h | rabbit | EPA OPP 81-5 (Acute Dermal Irritation) |

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | Result | Exposure | Species | Method |
|---|----------------|----------|---------|---|
| CAS-No. | | time | | |
| triethyl phosphate 78-40-0 | Category II | 24 h | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Trimethoxyvinylsilane 2768-02-7 | not irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Bis(2,2,6,6-tetramethyl-4- piperidyl) sebacate 52829-07-9 | corrosive | 24 h | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|--|-----------------|------------------------------|------------|---|
| Trimethoxyvinylsilane 2768-02-7 | sensitising | Buehler test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | not sensitising | Guinea pig maximisation test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|--|----------|--|--|---------|--|
| Trimethoxyvinylsilane 2768-02-7 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Trimethoxyvinylsilane 2768-02-7 | positive | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Trimethoxyvinylsilane 2768-02-7 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Trimethoxyvinylsilane 2768-02-7 | negative | intraperitoneal | | mouse | other guideline: |

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|--|---|-----------------------------|----------------------|---------|---|
| Trimethoxyvinylsilane 2768-02-7 | NOAEL P 250 mg/kg | one- generation study | oral: gavage | rat | OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422) |
| Trimethoxyvinylsilane 2768-02-7 | NOAEL P 1.000 mg/kg | one- generation study | oral: gavage | rat | OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422) |
| Trimethoxyvinylsilane 2768-02-7 | NOAEL F1 1.000 mg/kg | one- generation study | oral: gavage | rat | OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422) |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | NOAEL P 109 mg/kg NOAEL F1 121 mg/kg | two- generation study | oral: feed | rat | OECD Guideline 443 (Extended One-Generation Reproductive Toxicity Study) |

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Route of application | Exposure time / Frequency of treatment | Species | Method |
|--|--------------------|-----------------------|--|---------|---|
| triethyl phosphate 78-40-0 | NOAEL 100 mg/kg | oral: gavage | 28 days (4 weeks) daily | rat | EU Method B.7 (Repeated Dose (28 Days) Toxicity (Oral)) |
| Trimethoxyvinylsilane 2768-02-7 | NOAEL < 62,5 mg/kg | oral: gavage | 42d daily | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| Trimethoxyvinylsilane 2768-02-7 | NOAEL 0,605 mg/l | inhalation: vapour | 5 days/week for 14 weeks 6 hours/day | rat | not specified |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | NOAEL 36 mg/kg | oral: feed | daily | rat | other guideline: |

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|------------|---------------|---------------------|---|
| triethyl phosphate 78-40-0 | LC50 | > 100 mg/l | 96 h | Pimephales promelas | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Trimethoxyvinylsilane 2768-02-7 | LC50 | 191 mg/l | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | LC50 | 4,4 mg/l | 96 h | Lepomis macrochirus | OECD Guideline 203 (Fish, Acute Toxicity Test) |

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | Value | Value | Exposure time | Species | Method |
|----------------------------|-------|------------|---------------|---------------|-----------------------|
| CAS-No. | type | | | | |
| Trimethoxyvinylsilane | EC50 | 168,7 mg/l | 48 h | Daphnia magna | EU Method C.2 (Acute |
| 2768-02-7 | | | | | Toxicity for Daphnia) |
| Bis(2,2,6,6-tetramethyl-4- | EC50 | 8,58 mg/l | 48 h | Daphnia magna | OECD Guideline 202 |
| piperidyl) sebacate | | | | | (Daphnia sp. Acute |
| 52829-07-9 | | | | | Immobilisation Test) |

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | Value | Value | Exposure time | Species | Method |
|--|-------|-----------|---------------|---------------|--|
| CAS-No. | type | | | | |
| triethyl phosphate 78-40-0 | NOEC | 31,6 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| Trimethoxyvinylsilane 2768-02-7 | NOEC | 28,1 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | NOEC | 0,23 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | Value | Value | Exposure time | Species | Method |
|--|-------|------------|---------------|---|--|
| CAS-No. | type | | | | |
| triethyl phosphate 78-40-0 | EC50 | 900,8 mg/l | 72 h | Scenedesmus subspicatus (new name: Desmodesmus subspicatus) | DIN 38412-09 |
| triethyl phosphate 78-40-0 | EC10 | 80,3 mg/l | 72 h | Scenedesmus subspicatus (new name: Desmodesmus subspicatus) | DIN 38412-09 |
| Trimethoxyvinylsilane 2768-02-7 | EC50 | > 957 mg/l | 72 h | Desmodesmus subspicatus | EU Method C.3 (Algal Inhibition test) |
| Trimethoxyvinylsilane 2768-02-7 | NOEC | 957 mg/l | 72 h | Desmodesmus subspicatus | EU Method C.3 (Algal Inhibition test) |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | EC50 | 0,705 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | EC10 | 0,188 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | Value | Value | Exposure time | Species | Method |
|--|-------|------------|---------------|-------------------------------|--|
| CAS-No. | type | | | | |
| triethyl phosphate 78-40-0 | EC10 | 2.985 mg/l | 30 min | | not specified |
| Trimethoxyvinylsilane 2768-02-7 | EC50 | > 100 mg/l | | predominantly domestic sewage | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | EC50 | > 100 mg/l | 3 h | ζ., | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |

12.2. Persistence and degradability

| Hazardous substances CAS-No. | Result | Test type | Degradability | Exposure time | Method |
|--|---------------------------------|-----------|---------------|---------------|---|
| triethyl phosphate 78-40-0 | not readily biodegradable. | aerobic | 0,5 % | | OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test) |
| triethyl phosphate 78-40-0 | not inherently biodegradable | aerobic | 97 % | 28 d | OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test) |
| Trimethoxyvinylsilane 2768-02-7 | not readily biodegradable. | aerobic | 51 % | 28 d | OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test) |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 | not readily biodegradable. | aerobic | 24 % | 28 d | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

| Hazardous substances CAS-No. | LogPow | Temperature | Method |
|---|--------|-------------|--|
| triethyl phosphate 78-40-0 | 0,8 | | not specified |
| Bis(2,2,6,6-tetramethyl-4- piperidyl) sebacate 52829-07-9 | 0,35 | 25 °C | OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method) |

12.5. Results of PBT and vPvB assessment

| Hazardous substances | PBT / vPvB |
|---|--|
| CAS-No. | |
| triethyl phosphate | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very |
| 78-40-0 | Bioaccumulative (vPvB) criteria. |
| Trimethoxyvinylsilane | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very |
| 2768-02-7 | Bioaccumulative (vPvB) criteria. |
| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very |
| 52829-07-9 | Bioaccumulative (vPvB) criteria. |

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

08 04 10 Waste adhesives and sealants other than those mentioned in 08 04 09.

SECTION 14: Transport information

14.1. UN number or ID number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):

Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):

Persistent organic pollutants (Regulation (EU) 2019/1021):

VOC content

(2010/75/EU)

Not applicable
Not applicable

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

ED: Substance identified as having endocrine disrupting properties

EU OEL:

EU EXPLD 1:

Substance with a Union workplace exposure limit

EU EXPLD 1:

Substance listed in Annex I, Reg (EC) No. 2019/1148

EU EXPLD 2

Substance listed in Annex II, Reg (EC) No. 2019/1148

SVHC:

Substance of very high concern (REACH Candidate List)

PBT:

Substance fulfilling persistent, bioaccumulative and toxic criteria

PBT/vPvB: Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very

bioaccumulative criteria

vPvB: Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.