Printing: 03/11/2022 Date of compilation: 20/10/2021 Revised: 08/06/2022 Version: 2 (Replaced 1)

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**1.1 Product identifier:** PROFIRS 0RS099 TRACK BEDLINER

Other means of identification:

**UFI:** R356-S1G5-K00R-A0R7

## 1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Car repair; paints and varnishes. For professional users only. Uses advised against: All uses not specified in this section or in section 7.3

#### 1.3 Details of the supplier of the safety data sheet:

Troton Sp. z o.o. Ząbrowo 14A

78-120 Gościno - Zachodniopomorskie - Polska Phone: +48 94 35 123 94 - Fax: +48 94 35 126 22

troton@troton.com.pl www.troton.pl / www.troton.eu

**1.4 Emergency telephone number:** ( 8am-4pm)+48 094 35 123 94; 112

## **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1 Classification of the substance or mixture:

## CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Eye Irrit. 2: Eye irritation, Category 2, H319 Flam. Liq. 3: Flammable liquids, Category 3, H226

Repr. 2: Reproductive toxicity, Category 2, H361 Skin Irrit. 2: Skin irritation, Category 2, H315

Skin Sens. 1A: Sensitisation, skin, Category 1A, H317

STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Oral), H373

STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

## 2.2 Label elements:

## CLP Regulation (EC) No 1272/2008:

#### Warning







#### **Hazard statements:**

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 3: H226 - Flammable liquid and vapour.

Repr. 2: H361 - Suspected of damaging fertility or the unborn child.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

STOT SE 3: H335 - May cause respiratory irritation.

#### **Precautionary statements:**

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280: We ar protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P302+P352: IF ON SKIN: Wash with plenty of water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Substances that contribute to the classification

Printing: 03/11/2022 Date of compilation: 20/10/2021 Revised: 08/06/2022 Version: 2 (Replaced 1)

# SECTION 2: HAZARDS IDENTIFICATION (continued)

Xylene; 4-hydroxy-4-methylpentan-2-one; Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

## 2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

Endocrine-disrupting properties: The product fails to meet the criteria.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substance:

Non-applicable

#### 3.2 Mixture:

Chemical description: Mixture composed of chemical products

**Components:** 

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification		Chemical name/Classification		Concentration
1330-20-7 215-535-7 601-022-00-9 01-2119488216-32- XXXX	Xylene <sup>(1)</sup> Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	Self-classified	25 - <50 %
7727-43-7 231-784-4 Non-applicable 01-2119491274-35- XXXX	Regulation 1272/2008		Not classified	5 - <10 %
123-42-2 204-626-7 603-016-00-1 01-2119473975-21- XXXX	4-hydroxy-4-methyl	pentan-2-one(1)  Eye Irrit. 2: H319; Flam. Liq. 3: H226; Repr. 2: H361; STOT SE 3: H335 - Warning	Self-classified  (!)	2,5 - <5 %
7779-90-0 231-944-3 Non-applicable 01-2119485044-40- XXXX	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning	ATP CLP00	1 - <2,5 %
100-41-4 202-849-4 601-023-00-4 01-2119489370-35- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	ATP ATP06	<1 %
1065336-91-5 915-687-0 Non-applicable 01-2119491304-40- XXXX		(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl yl-4-piperidyl sebacate <sup>(1)</sup> Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Repr. 2: H361f; Skin Sens. 1A: H317 - Warning	Self-classified	<1 %
14808-60-7 238-878-4 Non-applicable Non-applicable	Quartz (1 %< RCS < Regulation 1272/2008	: 10%) <sup>(2)</sup> STOT RE 2: H373 - Warning	Self-classified	<1 %
108-65-6 203-603-9 607-195-00-7 01-2119475791-29- XXXX	2-methoxy-1-methyl Regulation 1272/2008	ethyl acetate <sup>(2)</sup> Flam. Liq. 3: H226 - Warning	ATP ATP01	<1 %
123-86-4 204-658-1 607-025-00-1 01-2119485493-29- XXXX	N-butyl acetate <sup>(2)</sup> Regulation 1272/2008	Flow Lie 20 H226, CTOT OF 20 H226, FUHIOCO Warning		<1 %
108-88-3 203-625-9 601-021-00-3 01-2119471310-51- XXXX	Toluene <sup>(2)</sup> Regulation 1272/2008	Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	Self-classified	<1 %

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

<sup>(2)</sup> Substance with a Union workplace exposure limit

Printing: 03/11/2022 Date of compilation: 20/10/2021 Revised: 08/06/2022 Version: 2 (Replaced 1)

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

#### Other information:

Identification	Specific concentration limit
4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7	% (w/w) >=10: Eye Irrit. 2 - H319

## **SECTION 4: FIRST AID MEASURES**

## 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

#### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

#### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

#### By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

## By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

## 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

## 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

## **SECTION 5: FIREFIGHTING MEASURES**

## 5.1 Extinguishing media:

## Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>).

## Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

#### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

## 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

## Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

Printing: 03/11/2022 Date of compilation: 20/10/2021 Revised: 08/06/2022 Version: 2 (Replaced 1)

# SECTION 6: ACCIDENTAL RELEASE MEASURES

## 6.1 Personal precautions, protective equipment and emergency procedures:

#### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

#### For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

## 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

## 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### 6.4 Reference to other sections:

See sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

# 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 15 °C

Maximum Temp.: 25 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

## 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

Printing: 03/11/2022 Date of compilation: 20/10/2021 Revised: 08/06/2022 Version: 2 (Replaced 1)

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occ	cupational exposu	ure limits
Xylene	IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>
CAS: 1330-20-7 EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>
Barium Sulfate	IOELV (8h)		0,5 mg/m <sup>3</sup>
CAS: 7727-43-7	IOELV (STEL)		
Ethylbenzene	IOELV (8h)	100 ppm	442 mg/m <sup>3</sup>
CAS: 100-41-4	IOELV (STEL)	200 ppm	884 mg/m <sup>3</sup>
Quartz (1 %< RCS < 10%)	IOELV (8h)		0,1 mg/m <sup>3</sup>
CAS: 14808-60-7	IOELV (STEL)		
2-methoxy-1-methylethyl acetate	IOELV (8h)	50 ppm	275 mg/m <sup>3</sup>
CAS: 108-65-6	IOELV (STEL)	100 ppm	550 mg/m <sup>3</sup>
N-butyl acetate	IOELV (8h)	50 ppm	241 mg/m <sup>3</sup>
CAS: 123-86-4	IOELV (STEL)	150 ppm	723 mg/m <sup>3</sup>
Toluene	IOELV (8h)	50 ppm	192 mg/m <sup>3</sup>
CAS: 108-88-3	IOELV (STEL)	100 ppm	384 mg/m <sup>3</sup>

## **DNEL (Workers):**

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	442 mg/m³	442 mg/m³	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>
Barium Sulfate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 7727-43-7	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 231-784-4	Inhalation	Non-applicable	Non-applicable	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
4-hydroxy-4-methylpentan-2-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-42-2	Dermal	Non-applicable	Non-applicable	467 mg/kg	Non-applicable
EC: 204-626-7	Inhalation	Non-applicable	240 mg/m <sup>3</sup>	32,6 mg/m <sup>3</sup>	Non-applicable
trizinc bis(orthophosphate)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 7779-90-0	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 231-944-3	Inhalation	Non-applicable	Non-applicable	5 mg/m³	Non-applicable
Ethylbenzene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	293 mg/m <sup>3</sup>	77 mg/m³	Non-applicable
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1065336-91-5	Dermal	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
EC: 915-687-0	Inhalation	Non-applicable	Non-applicable	0,68 mg/m <sup>3</sup>	Non-applicable
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	550 mg/m <sup>3</sup>	275 mg/m <sup>3</sup>	Non-applicable
N-butyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-86-4	Dermal	11 mg/kg	Non-applicable	11 mg/kg	Non-applicable
EC: 204-658-1	Inhalation	600 mg/m <sup>3</sup>	600 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>
Toluene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	384 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	384 mg/m <sup>3</sup>	384 mg/m <sup>3</sup>	192 mg/m <sup>3</sup>	192 mg/m <sup>3</sup>

## **DNEL (General population):**

Printing: 03/11/2022 Date of compilation: 20/10/2021 Revised: 08/06/2022 Version: 2 (Replaced 1)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)				
	A1 .			

		Short e	Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local	
Xylene	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable	
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable	
EC: 215-535-7	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>	
Barium Sulfate	Oral	Non-applicable	Non-applicable	13000 mg/kg	Non-applicable	
CAS: 7727-43-7	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
EC: 231-784-4	Inhalation	Non-applicable	Non-applicable	10 mg/m <sup>3</sup>	Non-applicable	
4-hydroxy-4-methylpentan-2-one	Oral	Non-applicable	Non-applicable	1,67 mg/kg	Non-applicable	
CAS: 123-42-2	Dermal	Non-applicable	Non-applicable	33 mg/kg	Non-applicable	
EC: 204-626-7	Inhalation	Non-applicable	Non-applicable	5,8 mg/m <sup>3</sup>	Non-applicable	
trizinc bis(orthophosphate)	Oral	Non-applicable	Non-applicable	0,83 mg/kg	Non-applicable	
CAS: 7779-90-0	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable	
EC: 231-944-3	Inhalation	Non-applicable	Non-applicable	2,5 mg/m <sup>3</sup>	Non-applicable	
Ethylbenzene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable	
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
EC: 202-849-4	Inhalation	Non-applicable	Non-applicable	15 mg/m <sup>3</sup>	Non-applicable	
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Oral	Non-applicable	Non-applicable	0,05 mg/kg	Non-applicable	
CAS: 1065336-91-5	Dermal	Non-applicable	Non-applicable	0,25 mg/kg	Non-applicable	
EC: 915-687-0	Inhalation	Non-applicable	Non-applicable	0,17 mg/m <sup>3</sup>	Non-applicable	
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable	
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable	
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m <sup>3</sup>	33 mg/m <sup>3</sup>	
N-butyl acetate	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable	
CAS: 123-86-4	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable	
EC: 204-658-1	Inhalation	300 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>	35,7 mg/m <sup>3</sup>	35,7 mg/m <sup>3</sup>	
Toluene	Oral	Non-applicable	Non-applicable	8,13 mg/kg	Non-applicable	
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	226 mg/kg	Non-applicable	
EC: 203-625-9	Inhalation	226 mg/m <sup>3</sup>	226 mg/m <sup>3</sup>	56,5 mg/m <sup>3</sup>	56,5 mg/m <sup>3</sup>	

## PNEC:

Identification				
Xylene	STP	6,58 mg/L	Fresh water	0,327 mg/L
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water	0,327 mg/L
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
Barium Sulfate	STP	62,2 mg/L	Fresh water	0,115 mg/L
CAS: 7727-43-7	Soil	207,7 mg/kg	Marine water	Non-applicable
EC: 231-784-4	Intermittent	Non-applicable	Sediment (Fresh water)	600,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable
4-hydroxy-4-methylpentan-2-one	STP	100 mg/L	Fresh water	2 mg/L
CAS: 123-42-2	Soil	0,3 mg/kg	Marine water	0,2 mg/L
EC: 204-626-7	Intermittent	1 mg/L	Sediment (Fresh water)	7,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,74 mg/kg
trizinc bis(orthophosphate)	STP	0,1 mg/L	Fresh water	0,0206 mg/L
CAS: 7779-90-0	Soil	35,6 mg/kg	Marine water	0,0061 mg/L
EC: 231-944-3	Intermittent	Non-applicable	Sediment (Fresh water)	117,8 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	56,5 mg/kg
Ethylbenzene	STP	9,6 mg/L	Fresh water	0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water	0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg

Printing: 03/11/2022 Date of compilation: 20/10/2021 Revised: 08/06/2022 Version: 2 (Replaced 1)

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	STP	1 mg/L	Fresh water	0,002 mg/L
CAS: 1065336-91-5	Soil	0,21 mg/kg	Marine water	0 mg/L
EC: 915-687-0	Intermittent	0,009 mg/L	Sediment (Fresh water)	1,05 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,11 mg/kg
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water	0,635 mg/L
CAS: 108-65-6	Soil	0,29 mg/kg	Marine water	0,064 mg/L
EC: 203-603-9	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
N-butyl acetate	STP	35,6 mg/L	Fresh water	0,18 mg/L
CAS: 123-86-4	Soil	0,09 mg/kg	Marine water	0,018 mg/L
EC: 204-658-1	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,098 mg/kg
Toluene	STP	13,61 mg/L	Fresh water	0,68 mg/L
CAS: 108-88-3	Soil	2,89 mg/kg	Marine water	0,68 mg/L
EC: 203-625-9	Intermittent	0,68 mg/L	Sediment (Fresh water)	16,39 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	16,39 mg/kg

#### 8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

# B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: A)	CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

## C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
	NON-disposable chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.4 mm)		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN ISO 21420:2020	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

## D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CATII	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

#### E.- Body protection

Printing: 03/11/2022 Date of compilation: 20/10/2021 Revised: 08/06/2022 Version: 2 (Replaced 1)

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	CAT III	EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

## F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
•	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	<b>→</b>	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

#### **Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

#### Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 35,77 % weight V.O.C. density at 20 °C: 530 kg/m $^3$  (530 g/L)

Average carbon number: 7,83

Average molecular weight: 107,24 g/mol

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES \*\*

## 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

#### Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Odour:

Not available

Non-applicable \*

**Volatility:** 

Boiling point at atmospheric pressure: 118 °C
Vapour pressure at 20 °C: 2083 Pa

Vapour pressure at 50 °C: 11005,88 Pa (11,01 kPa)

Evaporation rate at 20 °C: Non-applicable \*

**Product description:** 

Density at 20 °C: 1,3 kg/m³ Relative density at 20 °C: 1,181

Dynamic viscosity at 20 °C: Non-applicable  $^{\ast}$ 

\*Not relevant due to the nature of the product, not providing information property of its hazards.

<sup>\*\*</sup> Changes with regards to the previous version

Printing: 03/11/2022 Date of compilation: 20/10/2021 Revised: 08/06/2022 Version: 2 (Replaced 1)

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES \*\* (continued)

Kinematic viscosity at 20 °C: Non-applicable \* Kinematic viscosity at 40 °C: >20,5 mm<sup>2</sup>/s Concentration: Non-applicable \* Non-applicable \* Vapour density at 20 °C: Non-applicable \* Partition coefficient n-octanol/water 20 °C: Non-applicable \* Solubility in water at 20 °C: Non-applicable \* Solubility properties: Non-applicable \* Decomposition temperature: Non-applicable \* Melting point/freezing point: Non-applicable \*

Flammability:

Flash Point: 33 °C

Flammability (solid, gas): Non-applicable \*

Autoignition temperature: 315 °C

Lower flammability limit: Not available

Upper flammability limit: Not available

**Particle characteristics:** 

Median equivalent diameter: Non-applicable

#### 9.2 Other information:

## Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Corrosive to metals:

Heat of combustion:

Aerosols-total percentage (by mass) of flammable components:

Non-applicable \*

Non-applicable \*

Other safety characteristics:

Surface tension at 20 °C:

Refraction index:

Non-applicable \*

Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

## SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

## 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

## 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

## 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

<sup>\*\*</sup> Changes with regards to the previous version

Printing: 03/11/2022 Date of compilation: 20/10/2021 Revised: 08/06/2022 Version: 2 (Replaced 1)

## SECTION 10: STABILITY AND REACTIVITY (continued)

## 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

#### **Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
  - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

IARC: Xylene (3); Ethylbenzene (2B); Toluene (3); Carbon black (2B); Hydrocarbons, C9, aromatics (3); Quartz (1 % < RCS < 10%) (1)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Suspected of damaging fertility or the unborn child
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
  - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
  - Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

#### Other information:

Non-applicable

## Specific toxicology information on the substances:

Printing: 03/11/2022 Date of compilation: 20/10/2021 Revised: 08/06/2022 Version: 2 (Replaced 1)

# SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	A	cute toxicity	Genus
Xylene	LD50 oral	2100 mg/kg	Rat
CAS: 1330-20-7	LD50 dermal	1100 mg/kg	Rat
EC: 215-535-7	LC50 inhalation	11 mg/L (ATEi)	
4-hydroxy-4-methylpentan-2-one	LD50 oral	3002 mg/kg	Rat
CAS: 123-42-2	LD50 dermal	>2000 mg/kg	
EC: 204-626-7	LC50 inhalation	>20 mg/L	
trizinc bis(orthophosphate)	LD50 oral	>2000 mg/kg	
CAS: 7779-90-0	LD50 dermal	>2000 mg/kg	
EC: 231-944-3	LC50 inhalation	>5 mg/L	
Barium Sulfate	LD50 oral	>5000 mg/kg	Rat
CAS: 7727-43-7	LD50 dermal	>2000 mg/kg	
EC: 231-784-4	LC50 inhalation	>5 mg/L	
Ethylbenzene	LD50 oral	3500 mg/kg	Rat
CAS: 100-41-4	LD50 dermal	15354 mg/kg	Rabbit
EC: 202-849-4	LC50 inhalation	17,2 mg/L (4 h)	Rat
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	LD50 oral	3230 mg/kg	Rat
CAS: 1065336-91-5	LD50 dermal	>2000 mg/kg	
EC: 915-687-0	LC50 inhalation	>20 mg/L	
Quartz (1 %< RCS < 10%)	LD50 oral	>2000 mg/kg	
CAS: 14808-60-7	LD50 dermal	>2000 mg/kg	
EC: 238-878-4	LC50 inhalation	>5 mg/L	
2-methoxy-1-methylethyl acetate	LD50 oral	8532 mg/kg	Rat
CAS: 108-65-6	LD50 dermal	5100 mg/kg	Rat
EC: 203-603-9	LC50 inhalation	30 mg/L (4 h)	Rat
N-butyl acetate	LD50 oral	12789 mg/kg	Rat
CAS: 123-86-4	LD50 dermal	14112 mg/kg	Rabbit
EC: 204-658-1	LC50 inhalation	23,4 mg/L (4 h)	Rat
Toluene	LD50 oral	5580 mg/kg	Rat
CAS: 108-88-3	LD50 dermal	12124 mg/kg	Rat
EC: 203-625-9	LC50 inhalation	28,1 mg/L (4 h)	Rat

## 11.2 Information on other hazards:

## **Endocrine disrupting properties**

Endocrine-disrupting properties: The product fails to meet the criteria.

## Other information

Non-applicable

# SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

## 12.1 Toxicity:

## **Acute toxicity:**

Identification	Concentration		Species	Genus
Xylene	LC50	>10 - 100 mg/L (96 h)		Fish
CAS: 1330-20-7	EC50	>10 - 100 mg/L (48 h)		Crustacean
EC: 215-535-7	EC50	>10 - 100 mg/L (72 h)		Algae
Barium Sulfate	LC50	76000 mg/L (96 h)	Salmo gairdneri	Fish
CAS: 7727-43-7	EC50	Non-applicable		
EC: 231-784-4	EC50	Non-applicable		

Printing: 03/11/2022 Date of compilation: 20/10/2021 Revised: 08/06/2022 Version: 2 (Replaced 1)

# SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification		Concentration	Species	Genus
4-hydroxy-4-methylpentan-2-one	LC50	110 mg/L (96 h)	Oryzias latipes	Fish
CAS: 123-42-2	EC50	1000 mg/L (48 h)	Daphnia magna	Crustacean
EC: 204-626-7	EC50	1000 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
trizinc bis(orthophosphate)	LC50	>0.1 - 1 mg/L (96 h)		Fish
CAS: 7779-90-0	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
EC: 231-944-3	EC50	>0.1 - 1 mg/L (72 h)		Algae
Ethylbenzene	LC50	42,3 mg/L (96 h)	Pimephales promelas	Fish
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	LC50	0,9 mg/L (96 h)	Danio rerio	Fish
CAS: 1065336-91-5	EC50	Non-applicable		
EC: 915-687-0	EC50	1,7 mg/L (72 h)	Desmodesmus subspicatus	Algae
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
EC: 203-603-9	EC50	Non-applicable		
N-butyl acetate	LC50	Non-applicable		
CAS: 123-86-4	EC50	Non-applicable		
EC: 204-658-1	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
Toluene	LC50	13 mg/L (96 h)	Carassius auratus	Fish
CAS: 108-88-3	EC50	11,5 mg/L (48 h)	Daphnia magna	Crustacean
EC: 203-625-9	EC50	Non-applicable		

## **Chronic toxicity:**

Identification		Concentration	Species	Genus
Xylene	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
CAS: 1330-20-7 EC: 215-535-7	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
Barium Sulfate	NOEC	100 mg/L	Danio rerio	Fish
CAS: 7727-43-7 EC: 231-784-4	NOEC	Non-applicable		
4-hydroxy-4-methylpentan-2-one	NOEC	Non-applicable		
CAS: 123-42-2 EC: 204-626-7	NOEC	100 mg/L	Daphnia magna	Crustacean
Ethylbenzene	NOEC	Non-applicable		
CAS: 100-41-4 EC: 202-849-4	NOEC	0,96 mg/L	Ceriodaphnia dubia	Crustacean
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	NOEC	Non-applicable		
CAS: 1065336-91-5 EC: 915-687-0	NOEC	1 mg/L	Daphnia magna	Crustacean
2-methoxy-1-methylethyl acetate	NOEC	47,5 mg/L	Oryzias latipes	Fish
CAS: 108-65-6 EC: 203-603-9	NOEC	100 mg/L	Daphnia magna	Crustacean
N-butyl acetate	NOEC	Non-applicable		
CAS: 123-86-4 EC: 204-658-1	NOEC	23,2 mg/L	Daphnia magna	Crustacean

# 12.2 Persistence and degradability:

# **Substance-specific information:**

Identification	De	gradability	Biodegrada	bility
Xylene	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1330-20-7	COD	Non-applicable	Period	28 days
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %
4-hydroxy-4-methylpentan-2-one	BOD5	Non-applicable	Concentration	57.5 mg/L
CAS: 123-42-2	COD	Non-applicable	Period	28 days
EC: 204-626-7	BOD5/COD	Non-applicable	% Biodegradable	98,51 %
Ethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 100-41-4	COD	Non-applicable	Period	14 days
EC: 202-849-4	BOD5/COD	Non-applicable	% Biodegradable	90 %

Printing: 03/11/2022 Date of compilation: 20/10/2021 Revised: 08/06/2022 Version: 2 (Replaced 1)

# SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Degra	adability	Biodegradab	oility
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	BOD5	Non-applicable	Concentration	20 mg/L
CAS: 1065336-91-5	COD	Non-applicable	Period	28 days
EC: 915-687-0	BOD5/COD	Non-applicable	% Biodegradable	38 %
2-methoxy-1-methylethyl acetate	BOD5	Non-applicable	Concentration	785 mg/L
CAS: 108-65-6	COD	Non-applicable	Period	8 days
EC: 203-603-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
N-butyl acetate	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 123-86-4	COD	Non-applicable	Period	5 days
EC: 204-658-1	BOD5/COD	Non-applicable	% Biodegradable	84 %
Toluene	BOD5	2,5 g O2/g	Concentration	100 mg/L
CAS: 108-88-3	COD	Non-applicable	Period	14 days
EC: 203-625-9	BOD5/COD	Non-applicable	% Biodegradable	100 %

# 12.3 Bioaccumulative potential:

## **Substance-specific information:**

Identification		Bioaccur	mulation potential
Xylene		BCF	9
AS: 1330-20-7		Pow Log	2.77
EC: 215-535-7		Potential	Low
4-hydroxy-4-methylpentan-2-one		BCF	0.5
CAS: 123-42-2		Pow Log	
EC: 204-626-7		Potential	Low
ylbenzene		BCF	1
5: 100-41-4		Pow Log	3.15
EC: 202-849-4		Potential	Low
2-methoxy-1-methylethyl acetate		BCF	1
CAS: 108-65-6		Pow Log	0.43
EC: 203-603-9		Potential	Low
N-butyl acetate		BCF	4
CAS: 123-86-4		Pow Log	1.78
EC: 204-658-1		Potential	Low
Toluene		BCF	90
CAS: 108-88-3		Pow Log	2.73
EC: 203-625-9		Potential	Moderate

# 12.4 Mobility in soil:

Identification	Absorption/desorption		Volati	ility
Xylene	Koc	202	Henry	524,86 Pa·m³/mol
CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes
EC: 215-535-7	Surface tension	Non-applicable	Moist soil	Yes
4-hydroxy-4-methylpentan-2-one	Koc	1	Henry	Non-applicable
CAS: 123-42-2	Conclusion	Very High	Dry soil	Non-applicable
EC: 204-626-7	Surface tension	2,963E-2 N/m (25 °C)	Moist soil	Non-applicable
Ethylbenzene	Koc	520	Henry	798,44 Pa·m³/mol
CAS: 100-41-4	Conclusion	Moderate	Dry soil	Yes
EC: 202-849-4	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Koc	204400	Henry	0E+0 Pa·m³/mol
CAS: 1065336-91-5	Conclusion	Immobile	Dry soil	No
EC: 915-687-0	Surface tension	Non-applicable	Moist soil	No

Printing: 03/11/2022 Date of compilation: 20/10/2021 Revised: 08/06/2022 Version: 2 (Replaced 1)

## SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorpt	Absorption/desorption		ility
N-butyl acetate	Koc	Non-applicable	Henry	Non-applicable
CAS: 123-86-4	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 204-658-1	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Non-applicable
Toluene	Koc	178	Henry	672,8 Pa·m³/mol
CAS: 108-88-3	Conclusion	Moderate	Dry soil	Yes
EC: 203-625-9	Surface tension	2,793E-2 N/m (25 °C)	Moist soil	Yes

#### 12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

#### 12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

## 12.7 Other adverse effects:

Not described

## SECTION 13: DISPOSAL CONSIDERATIONS

## 13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)	
	waste paint and varnish containing organic solvents or other hazardous substances packaging containing residues of or contaminated by hazardous substances	Dangerous	

#### Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP10 Toxic for reproduction, HP4 Irritant — skin irritation and eye damage

# Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

## Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

# **SECTION 14: TRANSPORT INFORMATION**

## Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



14.1 UN number or ID number: UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
Labels: 3
14.4 Packing group: III

**14.4 Packing group:** III **14.5 Environmental hazards:** No

14.6 Special precautions for user

Special regulations: 163, 367, 650

Tunnel restriction code: D/E

Physico-Chemical properties: see section 9

Limited quantities: 5

14.7 Maritime transport in bulk according to IMO

according to IMO instruments:

Non-applicable

Transport of dangerous goods by sea:

Printing: 03/11/2022 Date of compilation: 20/10/2021 Revised: 08/06/2022 Version: 2 (Replaced 1)

## SECTION 14: TRANSPORT INFORMATION (continued)

With regard to IMDG 40-20:



14.1 UN number or ID number: UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
Labels: 3
14.4 Packing group: UII

14.4 Packing group: III14.5 Marine pollutant: No

14.6 Special precautions for user

Special regulations: 223, 955, 163, 367

EmS Codes: F-E, S-E Physico-Chemical properties: see section 9

Limited quantities: 5 L

Segregation group: Non-applicable **14.7 Maritime transport in bulk** Non-applicable

according to IMO instruments:

## Transport of dangerous goods by air:

With regard to IATA/ICAO 2022:



14.1 UN number or ID number: UN1263
 14.2 UN proper shipping name: PAINT
 14.3 Transport hazard class(es): 3
 Labels: 3

14.4 Packing group: III
14.5 Environmental hazards: No
14.6 Special precautions for user

Physico-Chemical properties: see section 9 **14.7 Maritime transport in bulk** Non-applicable

according to IMO instruments:

## SECTION 15: REGULATORY INFORMATION

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

## Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

# Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects. Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

Printing: 03/11/2022 Date of compilation: 20/10/2021 Revised: 08/06/2022 Version: 2 (Replaced 1)

## SECTION 15: REGULATORY INFORMATION (continued)

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

## Other legislation:

The product could be affected by sectorial legislation

#### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

## SECTION 16: OTHER INFORMATION

#### Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

## Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

Information on basic physical and chemical properties (SECTION 9):

· Flash Point

## Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.

H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects.

H373: May cause damage to organs through prolonged or repeated exposure (Oral).

H361: Suspected of damaging fertility or the unborn child.

H317: May cause an allergic skin reaction.

H226: Flammable liquid and vapour.

H319: Causes serious eye irritation.

## Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

#### CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Acute Tox. 4: H332 - Harmful if inhaled.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Repr. 2: H361 - Suspected of damaging fertility or the unborn child.

Repr. 2: H361d - Suspected of damaging the unborn child.

Repr. 2: H361f - Suspected of damaging fertility.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation).

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H335 - May cause respiratory irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

## Classification procedure:

Skin Irrit. 2: Calculation method

STOT SE 3: Calculation method

Aguatic Chronic 3: Calculation method

STOT RE 2: Calculation method

Repr. 2: Calculation method

Skin Sens. 1A: Calculation method

Flam. Liq. 3: Calculation method (2.6.4.3)

Eye Irrit. 2: Calculation method

#### Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

## **PROFIRS 0RS099 TRACK BEDLINER**

Printing: 03/11/2022 Date of compilation: 20/10/2021 Revised: 08/06/2022 Version: 2 (Replaced 1)

## SECTION 16: OTHER INFORMATION (continued)

## Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

## Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

## **Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50

EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.