



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
Valvoline™ DCT SYNTHETIC BLEND GEAR  
OIL

Version: 12.0

Revision Date: 14.12.2023

Print Date: 26/06/2025

---

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Trade name : Valvoline™ DCT  
SYNTHETIC BLEND GEAR OIL

Product code : 908726

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Use of the substance/mixture : Engine, gear & lubricating oil.

**1.3 Details of the supplier of the safety data sheet**

Company : Ellis Enterprises B.V., an affiliate of Valvoline Global  
Operations  
Wieldrechtseweg 39  
3316 BG Dordrecht  
Netherlands

Telephone : +31 (0)78 654 3500 (in the Netherlands), or contact your local  
CSR contact person

E-mail address of person : SDS@valvolineglobal.com  
responsible for the SDS

**1.4 Emergency telephone number**

00-800-825-8654, or contact your local emergency telephone number at 112

---

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Not a hazardous substance or mixture.

---



**SAFETY DATA SHEET**  
 according to Regulation (EC) No. 1907/2006  
 Valvoline™ DCT SYNTHETIC BLEND GEAR  
 OIL

Version: 12.0

Revision Date: 14.12.2023

Print Date: 26/06/2025

**2.2 Label elements**

**Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

**Additional Labelling**

EUH210 Safety data sheet available on request.

EUH208 Contains C14-C18 alpha-olefin epoxide, reaction products with boric acid. May produce an allergic reaction.

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

**Components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1 276-738-4 649-483-00-5 01-2119474889-13-xxxx	Asp. Tox. 1; H304	>= 80 - < 90
Mineral Oil	Not Assigned  01-2119484627-25-xxxx, 01-2119471299-27-xxxx, 01-2119487077-29-xxxx, 01-2119480132-48-xxxx	Asp. Tox. 1; H304	>= 5 - < 10
Reaction products of fatty acids, C14-C18 (branched and linear) and C18 (unsaturated) with	68784-17-8 272-225-4	Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 1 - < 2.5



**SAFETY DATA SHEET**  
 according to Regulation (EC) No. 1907/2006  
 Valvoline™ DCT SYNTHETIC BLEND GEAR  
 OIL

Version: 12.0

Revision Date: 14.12.2023

Print Date: 26/06/2025

tetraethylenepentamine (linear, branched,			
C14-C18 alpha-olefin epoxide, reaction products with boric acid	Not Assigned  01-2119976364-28-xxxx	Skin Sens. 1B; H317	>= 0.5 - < 1

For explanation of abbreviations see section 16.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

- General advice : Do not leave the victim unattended.
  
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
  
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
  
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
  
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

**4.2 Most important symptoms and effects, both acute and delayed**

- Symptoms : No symptoms known or expected.

**4.3 Indication of any immediate medical attention and special treatment needed**

- Treatment : No hazards which require special first aid measures.  
  
Treat symptomatically.



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
Valvoline™ DCT SYNTHETIC BLEND GEAR  
OIL

Version: 12.0

Revision Date: 14.12.2023

Print Date: 26/06/2025

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).  
Keep in suitable, closed containers for disposal.



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
Valvoline™ DCT SYNTHETIC BLEND GEAR  
OIL

Version: 12.0

Revision Date: 14.12.2023

Print Date: 26/06/2025

---

**6.4 Reference to other sections**

See sections: 7, 8, 11, 12 and 13.

---

**SECTION 7: Handling and storage**

**7.1 Precautions for safe handling**

- Advice on safe handling : Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

- Specific use(s) : No data available

---

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

Contains no substances with occupational exposure limit values.

**8.2 Exposure controls**

**Personal protective equipment**

- Eye/face protection : Eye wash bottle with pure water  
Tightly fitting safety goggles



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
Valvoline™ DCT SYNTHETIC BLEND GEAR  
OIL

Version: 12.0

Revision Date: 14.12.2023

Print Date: 26/06/2025

Hand protection	
Material	: neoprene, nitrile rubber
Break through time	: >= 240 min
Glove thickness	: >= 0.35 mm
Directive	: Equipment should conform to EN 374
Remarks	: The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	: No personal respiratory protective equipment normally required.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: amber
Odour	: oily
Odour Threshold	: No data available
pH	: Not applicable
Pour point	: < 0 °C
Boiling point/boiling range	: No data available No data available
Flash point	: 160 °C



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
Valvoline™ DCT SYNTHETIC BLEND GEAR  
OIL

Version: 12.0

Revision Date: 14.12.2023

Print Date: 26/06/2025

Method: Pensky-Martens closed cup

Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.849 g/cm <sup>3</sup> (15.6 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	34 mm <sup>2</sup> /s (40 °C)
Oxidizing properties	:	No data available

## 9.2 Other information

Self-ignition : No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
Valvoline™ DCT SYNTHETIC BLEND GEAR  
OIL

Version: 12.0

Revision Date: 14.12.2023

Print Date: 26/06/2025

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : No decomposition if stored and applied as directed.

**10.4 Conditions to avoid**

Conditions to avoid : excessive heat  
Heat, flames and sparks.

**10.5 Incompatible materials**

Materials to avoid : Halogenated compounds  
halogens  
Strong oxidizing agents

**10.6 Hazardous decomposition products**

No hazardous decomposition products are known.

---

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

**Acute toxicity**

Not classified based on available information.

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute  
inhalation toxicity  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: No mortality observed at this dose.

**Reaction products of fatty acids, C14-C18 (branched and linear) and C18 (unsaturated) with  
tetraethylenepentamine (linear, branched):**



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
Valvoline™ DCT SYNTHETIC BLEND GEAR  
OIL

Version: 12.0

Revision Date: 14.12.2023

Print Date: 26/06/2025

Acute oral toxicity : (Rat, male and female): 5,000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes  
Assessment: The substance or mixture has no acute oral toxicity

**C14-C18 alpha-olefin epoxide, reaction products with boric acid:**

Acute oral toxicity : LD50 (Rat): > 16,000 mg/kg  
Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: No mortality observed at this dose.

**Skin corrosion/irritation**

Not classified based on available information.

**Product:**

Remarks : May cause skin irritation and/or dermatitis.

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Species : Rabbit  
Result : No skin irritation

**Reaction products of fatty acids, C14-C18 (branched and linear) and C18 (unsaturated) with tetraethylenepentamine (linear, branched,):**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Irritating to skin.  
GLP : yes

**C14-C18 alpha-olefin epoxide, reaction products with boric acid:**

Species : Rabbit  
Result : Slight, transient irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Result : Slight, transient irritation



**Valvoline™**  
**Global**

**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
Valvoline™ DCT SYNTHETIC BLEND GEAR  
OIL

Version: 12.0

Revision Date: 14.12.2023

Print Date: 26/06/2025

Remarks : Expected based on components.

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Species : Rabbit  
Result : No eye irritation

**Reaction products of fatty acids, C14-C18 (branched and linear) and C18 (unsaturated) with tetraethylenepentamine (linear, branched,:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Irritating to eyes.  
GLP : yes

**C14-C18 alpha-olefin epoxide, reaction products with boric acid:**

Species : Rabbit  
Result : No eye irritation

**Respiratory or skin sensitisation**

**Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Test Type : Buehler Test  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.

**C14-C18 alpha-olefin epoxide, reaction products with boric acid:**

Test Type : Buehler Test  
Assessment : The product is a skin sensitiser, sub-category 1B.  
Method : OECD Test Guideline 406



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
Valvoline™ DCT SYNTHETIC BLEND GEAR  
OIL

Version: 12.0

Revision Date: 14.12.2023

Print Date: 26/06/2025

---

**Germ cell mutagenicity**

Not classified based on available information.

**Components:**

**C14-C18 alpha-olefin epoxide, reaction products with boric acid:**

Genotoxicity in vitro : Test Type: Ames test  
Test system: Salmonella typhimurium  
Metabolic activation: with and without metabolic activation  
Result: negative

**Carcinogenicity**

Not classified based on available information.

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

**Mineral Oil:**

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

May be fatal if swallowed and enters airways.

**Mineral Oil:**

May be fatal if swallowed and enters airways.



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
Valvoline™ DCT SYNTHETIC BLEND GEAR  
OIL

Version: 12.0

Revision Date: 14.12.2023

Print Date: 26/06/2025

**Further information**

**Product:**

Remarks : No data available

---

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

- Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOELR: >= 1,000 mg/l  
Exposure time: 14 d  
Species: Oncorhynchus mykiss (rainbow trout)
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL: 10 mg/l  
Exposure time: 21 d  
Species: Daphnia (water flea)  
Test substance: WAF



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
Valvoline™ DCT SYNTHETIC BLEND GEAR  
OIL

Version: 12.0

Revision Date: 14.12.2023

Print Date: 26/06/2025

Method: OECD Test Guideline 211

**C14-C18 alpha-olefin epoxide, reaction products with boric acid:**

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Test substance: WAF  
Remarks: No toxicity at the limit of solubility
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: WAF  
Remarks: No toxicity at the limit of solubility
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Test substance: WAF  
Remarks: No toxicity at the limit of solubility

**12.2 Persistence and degradability**

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

- Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

**C14-C18 alpha-olefin epoxide, reaction products with boric acid:**

- Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 26.7 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

**12.3 Bioaccumulative potential**

**Components:**

**Reaction products of fatty acids, C14-C18 (branched and linear) and C18 (unsaturated) with tetraethylenepentamine (linear, branched):**



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
Valvoline™ DCT SYNTHETIC BLEND GEAR  
OIL

Version: 12.0

Revision Date: 14.12.2023

Print Date: 26/06/2025

Partition coefficient: n-octanol/water : log Pow: 45.8 (25 °C)

**C14-C18 alpha-olefin epoxide, reaction products with boric acid:**

Partition coefficient: n-octanol/water : log Pow: 9.4

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**12.6 Other adverse effects**

**Product:**

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life.

---

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
Valvoline™ DCT SYNTHETIC BLEND GEAR  
OIL

Version: 12.0

Revision Date: 14.12.2023

Print Date: 26/06/2025

---

## SECTION 14: Transport information

### 14.1 UN number

ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA\_P : Not regulated as a dangerous good

### 14.2 UN proper shipping name

ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA\_P : Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA\_P : Not regulated as a dangerous good

### 14.4 Packing group

ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA (Cargo) : Not regulated as a dangerous good  
IATA\_P (Passenger) : Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
Valvoline™ DCT SYNTHETIC BLEND GEAR  
OIL

Version: 12.0

Revision Date: 14.12.2023

Print Date: 26/06/2025

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	: Not applicable
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	: Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	: Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	: Not applicable
Control of Major Accident Hazards Regulations 2015 (COMAH)	Not applicable

#### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

#### The components of this product are reported in the following inventories:

TCSI	: On the inventory, or in compliance with the inventory
TSCA	: All substances listed as active on the TSCA inventory
AIIC	: On the inventory, or in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
NZIoC	: On the inventory, or in compliance with the inventory



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
Valvoline™ DCT SYNTHETIC BLEND GEAR  
OIL

Version: 12.0

Revision Date: 14.12.2023

Print Date: 26/06/2025

## 15.2 Chemical safety assessment

No data available

### Inventories

All countries listed in the following table are covered by the relevant inventory:  
AllC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

## SECTION 16: Other information

### Full text of H-Statements

H304 : May be fatal if swallowed and enters airways.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H319 : Causes serious eye irritation.

### Full text of other abbreviations

Asp. Tox. : Aspiration hazard  
Eye Irrit. : Eye irritation  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
Valvoline™ DCT SYNTHETIC BLEND GEAR  
OIL

Version: 12.0

Revision Date: 14.12.2023

Print Date: 26/06/2025

Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

**Further information**

Internal information : 000000233790

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN