



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE DCT
SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Valvoline™ HYBRID VEHICLE DCT
SYNTHETIC BLEND GEAR OIL

Product code : 908827

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline Global
Operations
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands

Telephone : +31 (0)78 654 3500 (in the Netherlands), or contact your local
CSR contact person

E-mail address of person : SDS@valvolineglobal.com
responsible for the SDS

1.4 Emergency telephone number

00-800-825-8654, or contact your local emergency telephone number at 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Long-term (chronic) aquatic hazard,
Category 3

H412: Harmful to aquatic life with long lasting
effects.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE DCT
SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P273 Avoid release to the environment.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1 276-738-4 649-483-00-5 01-2119474889-13- xxxx	Asp. Tox. 1; H304	>= 50 - < 60
METHACRYLATE COPOLYMER	Not Assigned	Eye Irrit. 2; H319	>= 2.5 - < 5
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25- xxxx	Asp. Tox. 1; H304	>= 2.5 - < 5
2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol	1218787-32-6 01-2119510877-33- xxxx	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Acute 1;	>= 0.25 - < 0.5



SAFETY DATA SHEET
 according to Regulation (EC) No. 1907/2006
 Valvoline™ HYBRID VEHICLE DCT
 SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

		H400 Aquatic Chronic 2; H411 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	
3-((C9-11-iso,C10-rich)alkyloxy)propan-1-amine	Not Assigned 01-2119974116-35-xxxx	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10	$\geq 0.025 - < 0.1$
N-OLEYL-1,3-PROPANEDIAMINE	7173-62-8 230-528-9	Met. Corr. 1; H290 Acute Tox. 4; H302 Eye Dam. 1; H318 STOT RE 1; H372 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10	$\geq 0.0025 - < 0.025$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.
 Protect unharmed eye.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE DCT
SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE DCT
SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.
Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform
respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the
application area.
Advice on protection against fire and explosion : Normal measures for preventive fire protection.
Hygiene measures : General industrial hygiene practice.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Containers which are opened must be carefully resealed and
kept upright to prevent leakage. Electrical installations /
working materials must comply with the technological safety
standards.
Advice on common storage : No materials to be especially mentioned.
Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE DCT
SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Eye/face protection	:	Safety glasses
Hand protection		
Material	:	neoprene, nitrile rubber
Break through time	:	>= 240 min
Glove thickness	:	>= 0.35 mm
Directive	:	Equipment should conform to EN 374
Remarks	:	The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove.
Skin and body protection	:	Protective suit
Respiratory protection	:	No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	amber
Odour	:	oily
Odour Threshold	:	No data available
pH	:	Not applicable



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE DCT
SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

Melting point/freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	ca. 178 °C Method: Pensky-Martens closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	ca. 0.847 g/cm ³ (15.6 °C)
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	ca. 32.7 mm ² /s (40 °C) Method: ASTM D 445
Oxidizing properties	:	No data available

9.2 Other information

Self-ignition	:	No data available
---------------	---	-------------------



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE DCT
SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.
No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : excessive heat

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE DCT
SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol:

Acute oral toxicity : LD50 (Rat, female): 1,200 mg/kg
Method: OECD Test Guideline 425

3-((C9-11-iso,C10-rich)alkyloxy)propan-1-amine:

Acute oral toxicity : LD50 (Rat): 200 - 2,000 mg/kg
Method: OECD Test Guideline 423
Assessment: The component/mixture is moderately toxic after single ingestion.

N-OLEYL-1,3-PROPANEDIAMINE:

Acute oral toxicity : LD50 (Rat, female): ca. 500 mg/kg
Method: OECD Test Guideline 423

Skin corrosion/irritation

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species : Rabbit
Result : No skin irritation

METHACRYLATE COPOLYMER:

Result : Slight, transient irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol:

Result : Corrosive after 1 to 4 hours of exposure

3-((C9-11-iso,C10-rich)alkyloxy)propan-1-amine:



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE DCT
SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 3 minutes to 1 hour of exposure

N-OLEYL-1,3-PROPANEDIAMINE:

Result : Corrosive to skin
Remarks : Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species : Rabbit
Result : No eye irritation

METHACRYLATE COPOLYMER:

Result : Irritating to eyes.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : No eye irritation
Result : No eye irritation

N-OLEYL-1,3-PROPANEDIAMINE:

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE DCT
SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

Germ cell mutagenicity

Not classified based on available information.

Components:

N-OLEYL-1,3-PROPANEDIAMINE:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay)
Result: negative

Test system: Chinese hamster lung cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster fibroblasts
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE DCT
SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

N-OLEYL-1,3-PROPANEDIAMINE:

Assessment : Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

May be fatal if swallowed and enters airways.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE DCT
SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Toxicity to fish	: LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOELR: >= 1,000 mg/l Exposure time: 14 d Species: Oncorhynchus mykiss (rainbow trout)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL: 10 mg/l Exposure time: 21 d Species: Daphnia (water flea) Test substance: WAF Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity	: Not classified based on available information.
Chronic aquatic toxicity	: Not classified based on available information.

METHACRYLATE COPOLYMER:

Ecotoxicology Assessment

Acute aquatic toxicity	: Not classified based on available information.
Chronic aquatic toxicity	: Not classified based on available information.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE DCT
SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish	:	LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	:	NOEC: 10 mg/l Species: Fish
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 10 mg/l Species: Aquatic invertebrates

Ecotoxicology Assessment

Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.

2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol:

Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): 0.1 mg/l Exposure time: 96 h Test Type: semi-static test Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 0.043 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 0.0867 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Method: OECD Test Guideline 201 NOEC (Pseudokirchneriella subcapitata (green algae)): 0.0156 mg/l Exposure time: 72 h



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE DCT
SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

M-Factor (Acute aquatic toxicity) : 10

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50: 0.0463 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 1; Very toxic to aquatic life.

Chronic aquatic toxicity : Chronic aquatic toxicity Category 2; Toxic to aquatic life with long lasting effects.

3-((C9-11-iso,C10-rich)alkyloxy)propan-1-amine:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 2.14 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 0.0827 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 10

Ecotoxicology Assessment

Acute aquatic toxicity :
Acute aquatic toxicity Category 1; Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.
Chronic aquatic toxicity Category 1; Very toxic to aquatic life with long lasting effects.

N-OLEYL-1,3-PROPANEDIAMINE:



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE DCT
SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

Toxicity to fish	: LC50 (Danio rerio (zebra fish)): 0.1 mg/l Exposure time: 96 h Test Type: semi-static test Remarks: The toxicological data has been taken from products of similar composition.
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 0.025 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: EC50 (Desmodesmus subspicatus (green algae)): 0.506 mg/l Exposure time: 72 h Test Type: static test Method: OECD Test Guideline 201
M-Factor (Acute aquatic toxicity)	: 10
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: 0.1 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Test Type: semi-static test

Ecotoxicology Assessment

Acute aquatic toxicity	: Very toxic to aquatic life.
Chronic aquatic toxicity	: Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 2 - 4 % Exposure time: 28 d Method: OECD Test Guideline 301B
------------------	--

2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol:

Biodegradability	: Inoculum: activated sludge Concentration: 2.7 mg/l Result: Readily biodegradable. Biodegradation: 63 % Related to: Chemical oxygen demand
------------------	---



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE DCT
SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

Exposure time: 28 d
Method: OECD Test Guideline 301D

3-((C9-11-iso,C10-rich)alkyloxy)propan-1-amine:

Biodegradability : Inoculum: activated sludge
Result: Readily biodegradable.
Biodegradation: 68 %
Exposure time: 28 d

N-OLEYL-1,3-PROPANEDIAMINE:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 62 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

12.3 Bioaccumulative potential

Components:

3-((C9-11-iso,C10-rich)alkyloxy)propan-1-amine:

Partition coefficient: n-octanol/water : log Pow: -0.34 (25 °C)

N-OLEYL-1,3-PROPANEDIAMINE:

Partition coefficient: n-octanol/water : log Pow: 0.03 (25.7 °C)
pH: 6.8

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE DCT
SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

Additional ecological information : (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.

SECTION 14: Transport information

14.1 UN number

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA_P : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA_P : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA_P : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE DCT
SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA_P (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered:
Number on list 3
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable
UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable
Control of Major Accident Hazards Regulations 2015 (COMAH) : Not applicable

The components of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory
TSCA : All substances listed as active on the TSCA inventory
AIIC : Not in compliance with the inventory



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE DCT
SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

DSL	:	All components of this product are on the Canadian DSL
ENCS	:	Not in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
NZIoC	:	Not in compliance with the inventory

15.2 Chemical safety assessment

No data available

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16: Other information

Full text of H-Statements

H290	:	May be corrosive to metals.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H314	:	Causes severe skin burns and eye damage.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H372	:	Causes damage to organs through prolonged or repeated exposure.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Met. Corr.	:	Corrosive to metals



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Valvoline™ HYBRID VEHICLE DCT

SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

Skin Corr. : Skin corrosion
STOT RE : Specific target organ toxicity - repeated exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Internal information : 000000277162

Classification of the mixture:

Aquatic Chronic 3

H412

Classification procedure:

Based on product data or assessment



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Valvoline™ HYBRID VEHICLE DCT

SYNTHETIC BLEND GEAR OIL

Version: 3.0

Revision Date: 21.09.2023

Print Date: 26/06/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN