

**BREMBO N.V.**

Revision nr. 9

Dated 13/12/2023

Printed on 13/12/2023

Page n. 2/17

Replaced revision:8 (Printed on: 17/01/2023)

BRAKE FLUID DOT 4 LV

Hazard pictograms:



Signal words: Warning

Hazard statements:

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

Precautionary statements:

P280 Wear protective gloves/ protective clothing / eye protection / face protection.**P201** Obtain special instructions before use.**P308+P313** IF exposed or concerned: Get medical advice / attention.**Contains:** tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] borate**2.3. Other hazards**On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.**SECTION 3. Composition/information on ingredients****3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] borate		
INDEX -	$45 \leq x < 50$	Repr. 2 H361fd
EC 250-418-4		
CAS 30989-05-0		
REACH Reg. 01-2119462824-33-xxxx		
Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol		
INDEX -	$15 \leq x < 20$	Eye Dam. 1 H318
EC 907-996-4		Eye Dam. 1 H318: $\geq 30\%$, Eye Irrit. 2 H319: $\geq 20\%$
CAS -		
REACH Reg. 01-2119475115-41-xxxx		
TRIETHYLENE GLYCOL		
INDEX -	$1 \leq x < 3$	Substance with a community workplace exposure limit.
EC 203-953-2		



BREMBO N.V.

Revision nr. 9

Dated 13/12/2023

Printed on 13/12/2023

Page n. 3/17

Replaced revision:8 (Printed on: 17/01/2023)

BRAKE FLUID DOT 4 LV

CAS 112-27-6

REACH Reg. 01-2119438366-35-
xxxx

2,6-di-tert-butyl-p-cresol

INDEX - 0,1 ≤ x < 0,2 Aquatic Chronic 1 H410 M=1

EC 204-881-4

CAS 128-37-0

REACH Reg. 01-2119480433-40-
xxxx

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained



BREMBO N.V.

Revision nr. 9

Dated 13/12/2023

Printed on 13/12/2023

Page n. 4/17

Replaced revision:8 (Printed on: 17/01/2023)

BRAKE FLUID DOT 4 LV

open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2022

**BREMBO N.V.**

Revision nr. 9

Dated 13/12/2023

Printed on 13/12/2023

Page n. 5/17

Replaced revision:8 (Printed on: 17/01/2023)

BRAKE FLUID DOT 4 LV**tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] borate**

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,211	mg/l
Normal value in marine water	0,021	mg/l
Normal value for fresh water sediment	0,76	mg/kg
Normal value for marine water sediment	0,076	mg/kg
Normal value for water, intermittent release	2,112	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	0,028	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation				7,2 mg/m ³				29,1 mg/m ³

2-(2-(2-methoxyethoxy)ethoxy)ethanol**Threshold Limit Value**

Type	Country	TWA/8h	STEL/15min	Remarks / Observations		
		mg/m ³	ppm	mg/m ³	ppm	
TLV-ACGIH		50				

Predicted no-effect concentration - PNEC

Normal value in fresh water	10	mg/l
Normal value in marine water	1	mg/l
Normal value for fresh water sediment	36,6	mg/kg
Normal value for marine water sediment	3,66	mg/kg
Normal value for water, intermittent release	50	mg/l
Normal value of STP microorganisms	200	mg/l
Normal value for the food chain (secondary poisoning)	89	mg/kg
Normal value for the terrestrial compartment	1,56	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	2 mg/kg				10 mg/kg bw/d
Inhalation			VND	93 mg/m ³			VND	156 mg/m ³
Skin			VND	100 mg/kg			VND	167 mg/kg bw/d

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Predicted no-effect concentration - PNEC

Normal value in fresh water	2	mg/l
Normal value in marine water	0,2	mg/l
Normal value for fresh water sediment	6,6	mg/kg
Normal value for marine water sediment	0,66	mg/kg
Normal value for water, intermittent release	18	mg/l
Normal value of STP microorganisms	500	mg/l

**BREMBO N.V.**

Revision nr. 9

Dated 13/12/2023

Printed on 13/12/2023

Page n. 6/17

Replaced revision:8 (Printed on: 17/01/2023)

BRAKE FLUID DOT 4 LV

Normal value for the food chain (secondary poisoning) 333 mg/kg

Normal value for the terrestrial compartment 0,46 mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				12,5 mg/kg bw/d				
Inhalation				117 mg/m3				195 mg/m3
Skin				125 mg/kg bw/d				208 mg/kg bw/d

TRIETHYLENE GLYCOL**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
OEL	EU	1000				

Predicted no-effect concentration - PNEC

Normal value in fresh water 10 mg/l

Normal value in marine water 1 mg/l

Normal value for fresh water sediment 46 mg/kg

Normal value of STP microorganisms 10 mg/l

Normal value for the terrestrial compartment 3,32 mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation			25 mg/m3	VND			50 mg/m3	VND
Skin			VND	20 mg/kg/d			VND	40 mg/kg/d

2,6-di-tert-butyl-p-cresol**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH		2				

Predicted no-effect concentration - PNEC

Normal value in fresh water 0,199 µg/l

Normal value in marine water 0,02 µg/l

Normal value for fresh water sediment 99,6 µG/kg

Normal value for marine water sediment 9,96 µG/kg

Normal value for water, intermittent release 1,99 µg/l

Normal value of STP microorganisms 0,17 mg/l

Normal value for the food chain (secondary poisoning) 8,33 mg/kg

Normal value for the terrestrial compartment 47,69 µG/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic

**BREMBO N.V.**

Revision nr. 9

Dated 13/12/2023

Printed on 13/12/2023

Page n. 7/17

Replaced revision:8 (Printed on: 17/01/2023)

BRAKE FLUID DOT 4 LV

Oral	1 mg/kg bw/d	0,25 mg/kg bw/d		
Inhalation	3,1 mg/m3	0,78 mg/m3	18 mg/m3	4,4 mg/m3
Skin	6,7 mg/kg bw/d	1,7 mg/kg bw/d	19 mg/kg bw/d	4,7 mg/kg bw/d

METHYL-1H-BENZOTRIAZOLE

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,008	mg/l
Normal value in marine water	0,008	mg/l
Normal value for fresh water sediment	0,0025	mg/kg
Normal value for marine water sediment	0,0025	mg/kg
Normal value for water, intermittent release	0,086	mg/l
Normal value of STP microorganisms	39,4	mg/l
Normal value for the terrestrial compartment	0,0024	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	0,25 mg/kg				
Inhalation			VND	4,4 mg/m3			VND	8,8 mg/m3
Skin			VND	0,25 mg/kg			VND	0,5 mg/kg

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

**BREMBO N.V.**

Revision nr. 9

Dated 13/12/2023

Printed on 13/12/2023

Page n. 8/17

Replaced revision:8 (Printed on: 17/01/2023)

BRAKE FLUID DOT 4 LV**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Properties	Value	Information
Appearance	liquid	
Colour	colourless to amber	
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	> 260 °C	
Flammability	not available	
Lower explosive limit	not applicable	
Upper explosive limit	not applicable	
Flash point	> 100 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	9	
Kinematic viscosity	not available	
Dynamic viscosity	750	
Solubility	soluble	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1,000 - 1,100	
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information**9.2.1. Information with regard to physical hazard classes**

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU) 0



BREMBO N.V.

Revision nr. 9

Dated 13/12/2023

Printed on 13/12/2023

Page n. 9/17

Replaced revision:8 (Printed on: 17/01/2023)

BRAKE FLUID DOT 4 LV

VOC (volatile carbon)

0

SECTION 10. Stability and reactivity

10.1. Reactivity

The product may react exothermically on contact with strong oxidising or reducing agents, strong acids or bases.

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Hygroscopic.

10.2. Chemical stability

Excessively high temperatures can cause thermal decomposition.

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Avoid exposure to: air.

Hygroscopic.

10.3. Possibility of hazardous reactions

See paragraph 10.1.

10.4. Conditions to avoid

Avoid overheating.

10.5. Incompatible materials

Oxidising or reducing agents. Strong acids or bases.

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Avoid contact with: strong acids, strong bases, water.

2,6-di-tert-butyl-p-cresol

Avoid contact with: oxidising agents.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Develops: carbon monoxide, carbon dioxide.

2,6-di-tert-butyl-p-cresol



BREMBO N.V.

Revision nr. 9

Dated 13/12/2023

Printed on 13/12/2023

Page n. 10/17

Replaced revision:8 (Printed on: 17/01/2023)

BRAKE FLUID DOT 4 LV

In decomposition develops: carbon oxides.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	Not classified (no significant component)

tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] borate

LD50 (Dermal):	> 2000 mg/kg
LD50 (Oral):	> 2000 mg/kg

2-(2-(2-methoxyethoxy)ethoxy)ethanol

LD50 (Dermal):	7,1 g/kg
----------------	----------



BREMBO N.V.

Revision nr. 9

Dated 13/12/2023

Printed on 13/12/2023

Page n. 11/17

Replaced revision:8 (Printed on: 17/01/2023)

BRAKE FLUID DOT 4 LV

LD50 (Oral): > 10500 mg/kg

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

LD50 (Dermal): 3540 mg/kg bw
LD50 (Oral): 5170 mg/kg bw

TRIETHYLENE GLYCOL

LD50 (Dermal): 16 ml/kg bw
LD50 (Oral): > 2000 mg/kg bw
LC50 (Inhalation vapours): > 5,2 mg/l

2,6-di-tert-butyl-p-cresol

LD50 (Dermal): > 2000 mg/kg dw
LD50 (Oral): > 2930 mg/kg dw

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Suspected of damaging fertility - Suspected of damaging the unborn child



BREMBO N.V.

Revision nr. 9

Dated 13/12/2023

Printed on 13/12/2023

Page n. 12/17

Replaced revision:8 (Printed on: 17/01/2023)

BRAKE FLUID DOT 4 LV

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

2,6-di-tert-butyl-p-cresol
EC50 - for Crustacea > 0,61 mg/l/48h
Chronic NOEC for Crustacea 0,316 mg/l

TRIETHYLENE GLYCOL
LC50 - for Fish 69800 mg/l/96h
EC50 - for Crustacea > 10000 mg/l/48h

2-(2-(2-methoxyethoxy)ethoxy)ethanol
LC50 - for Fish 10000 mg/l/96h
EC50 - for Crustacea > 500 mg/l/48h
Chronic NOEC for Crustacea 3152 mg/l
Chronic NOEC for Algae / Aquatic Plants 1000 mg/l

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

**BRAKE FLUID DOT 4 LV**

LC50 - for Fish	> 1800 mg/l/96h
EC50 - for Crustacea	> 3200 mg/l/48h
EC50 - for Algae / Aquatic Plants	391 mg/l/72h
EC10 for Algae / Aquatic Plants	188 mg/l/72h

tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl]
borate

LC50 - for Fish	> 222,2 mg/l/96h
EC50 - for Crustacea	> 211,2 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 224,4 mg/l/72h

12.2. Persistence and degradability

2,6-di-tert-butyl-p-cresol
NOT rapidly degradable

TRIETHYLENE GLYCOL

Rapidly degradable
2-(2-(2-methoxyethoxy)ethoxy)ethanol

Rapidly degradable
tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl]
borate

Rapidly degradable

12.3. Bioaccumulative potential

TRIETHYLENE GLYCOL

Partition coefficient: n-octanol/water -1,75

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Partition coefficient: n-octanol/water 0,51

12.4. Mobility in soil

TRIETHYLENE GLYCOL

Partition coefficient: soil/water 1

tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl]
borate

Partition coefficient: soil/water 0,008

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects



BREMBO N.V.

Revision nr. 9

Dated 13/12/2023

Printed on 13/12/2023

Page n. 14/17

Replaced revision:8 (Printed on: 17/01/2023)

BRAKE FLUID DOT 4 LV

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable



BREMBO N.V.

Revision nr. 9

Dated 13/12/2023

Printed on 13/12/2023

Page n. 15/17

Replaced revision:8 (Printed on: 17/01/2023)

BRAKE FLUID DOT 4 LV

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None



BREMBO N.V.

Revision nr. 9

Dated 13/12/2023

Printed on 13/12/2023

Page n. 16/17

Replaced revision:8 (Printed on: 17/01/2023)

BRAKE FLUID DOT 4 LV

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] borate

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

TRIETHYLENE GLYCOL

2,6-di-tert-butyl-p-cresol

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Repr. 2	Reproductive toxicity, category 2
Eye Dam. 1	Serious eye damage, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H318	Causes serious eye damage.
H410	Very toxic to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit



BREMBO N.V.

Revision nr. 9

Dated 13/12/2023

Printed on 13/12/2023

Page n. 17/17

Replaced revision:8 (Printed on: 17/01/2023)

BRAKE FLUID DOT 4 LV

- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2019/521 (XII Atp. CLP)
 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
 17. Regulation (EU) 2019/1148
 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.
This document must not be regarded as a guarantee on any specific product property.
The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.
Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

msds for B2C.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 09 / 11 / 12 / 15 / 16.