

Page 1 of 22
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 10.03.2021 / 0020
Replacing version dated / version: 02.12.2020 / 0019
Valid from: 10.03.2021
PDF print date: 15.06.2021
Active Primer

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Active Primer

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Priming

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU10 - Formulation (mixing) of preparations and/or re-packaging (excluding alloys)

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC 3 - Air care products

Process category [PROC]:

PROC 5 - Mixing or blending in batch processes

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC19 - Manual activities involving hand contact

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 2 - Formulation into mixture

ERC 5 - Use at industrial site leading to inclusion into/onto article

ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC 8c - Widespread use leading to inclusion into/onto article (indoor)

ERC 8f - Widespread use leading to inclusion into/onto article (outdoor)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH

Jerg-Wieland-Str. 4

89081 Ulm-Lehr

Tel.: (+49) 0731-1420-0

Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.03.2021 / 0020

Replacing version dated / version: 02.12.2020 / 0019

Valid from: 10.03.2021

PDF print date: 15.06.2021

Active Primer

| Hazard class | Hazard category | Hazard statement |
|--------------|-----------------|---|
| Flam. Liq. | 2 | H225-Highly flammable liquid and vapour. |
| Eye Irrit. | 2 | H319-Causes serious eye irritation. |
| Resp. Sens. | 1 | H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| Skin Sens. | 1 | H317-May cause an allergic skin reaction. |
| STOT SE | 3 | H336-May cause drowsiness or dizziness. |

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H225-Highly flammable liquid and vapour. H319-Causes serious eye irritation. H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317-May cause an allergic skin reaction. H336-May cause drowsiness or dizziness.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261-Avoid breathing vapours or spray. P280-Wear protective gloves and eye protection / face protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312-Call a POISON CENTRE / doctor if you feel unwell.

P403+P233-Store in a well-ventilated place. Keep container tightly closed. P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH204-Contains isocyanates. May produce an allergic reaction.

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

As from 24 August 2023 adequate training is required before industrial or professional use.

n-butyl acetate

Butanone

Polyisocyanate, aliphatic

Diphenylmethanediisocyanate, isomeres and homologues

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Page 3 of 22
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 10.03.2021 / 0020
Replacing version dated / version: 02.12.2020 / 0019
Valid from: 10.03.2021
PDF print date: 15.06.2021
Active Primer

| Butanone | Substance for which an EU exposure limit value applies. |
|--|---|
| Registration number (REACH) | --- |
| Index | 606-002-00-3 |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 201-159-0 |
| CAS | 78-93-3 |
| content % | 50-70 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 |

| 2-methoxy-1-methylethyl acetate | Substance for which an EU exposure limit value applies. |
|--|---|
| Registration number (REACH) | --- |
| Index | 607-195-00-7 |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 203-603-9 |
| CAS | 108-65-6 |
| content % | 5-15 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Flam. Liq. 3, H226 |

| Polyisocyanate, aliphatic | |
|--|---|
| Registration number (REACH) | --- |
| Index | --- |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 500-060-2 |
| CAS | 28182-81-2 |
| content % | 5-10 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Acute Tox. 4, H332 Skin Sens. 1, H317 STOT SE 3, H335 |

| n-butyl acetate | Substance for which an EU exposure limit value applies. |
|--|---|
| Registration number (REACH) | --- |
| Index | 607-025-00-1 |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 204-658-1 |
| CAS | 123-86-4 |
| content % | 1-5 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Flam. Liq. 3, H226 STOT SE 3, H336 |

| Xylene | Substance for which an EU exposure limit value applies. |
|--|---|
| Registration number (REACH) | --- |
| Index | 601-022-00-9 |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 215-535-7 |
| CAS | 1330-20-7 |
| content % | 1-5 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Flam. Liq. 3, H226 Acute Tox. 4, H332 Acute Tox. 4, H312 Skin Irrit. 2, H315 |

| Diphenylmethanediisocyanate, isomeres and homologues | |
|--|--|
| Registration number (REACH) | --- |
| Index | --- |
| EINECS, ELINCS, NLP, REACH-IT List-No. | --- |
| CAS | 9016-87-9 |
| content % | 0,5-<1 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 4, H332 Resp. Sens. 1, H334 STOT SE 3, H335 Carc. 2, H351 STOT RE 2, H373 (respiratory system) (as inhalation) |

Page 4 of 22
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 10.03.2021 / 0020
Replacing version dated / version: 02.12.2020 / 0019
Valid from: 10.03.2021
PDF print date: 15.06.2021
Active Primer

The substances named in this section are given with their actual, appropriate classification!
For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.
If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
Give copious water to drink - consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
The following may occur:

In case of sensitivity, concentrations below the limit value may already result in asthmatic symptoms.
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂
Sand
Extinction powder

Unsuitable extinguishing media

Water
High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:
Oxides of carbon
Oxides of nitrogen
Hydrocyanic acid (hydrogen cyanide)
Toxic pyrolysis products.
Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Page 5 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0020
 Replacing version dated / version: 02.12.2020 / 0019
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Active Primer

Remove possible causes of ignition - do not smoke.
 Ensure sufficient ventilation.
 Avoid inhalation, and contact with eyes or skin.
 If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.
 Resolve leaks if this possible without risk.
 Prevent surface and ground-water infiltration, as well as ground penetration.
 Prevent from entering drainage system.
 If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.
 Do not wash away with water or watery cleaning agents.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
 Avoid aerosol formation.
 Avoid inhalation of the vapours.
 Keep away from sources of ignition - Do not smoke.
 Take measures against electrostatic charging, if appropriate.
 Avoid contact with eyes or skin.
 No contact with products of this type in case of allergies, asthma und chronic respiratory tract disorders.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Store product closed and only in original packing.
 Not to be stored in gangways or stair wells.
 Do not store with flammable or self-igniting materials.
 Store cool.
 Store in a dry place.
 Only store at temperatures from $> 0^{\circ}\text{C}$ to $< 35^{\circ}\text{C}$.
 Observe special storage conditions.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| Chemical Name | Butanone | Content %:50-70 |
|---|--|-----------------|
| WEL-TWA: 200 ppm (600 mg/m ³) (WEL, EU) | WEL-STEL: 300 ppm (899 mg/m ³) (WEL), 300 ppm (900 mg/m ³) (EU) | --- |
| Monitoring procedures: | - Compur - KITA-122 SA(C) (549 277) - Compur - KITA-139 SB (549 731) - Compur - KITA-139 U (549 749) | |

Page 6 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0020
 Replacing version dated / version: 02.12.2020 / 0019
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Active Primer

| | |
|---|-----------------------|
| DFG Meth.-Nr. 4 (D) (Lösungsmittelgemische 4), DFG (E) (Solvent mixtures 4) - 2015, 2002 - INSHT MTA/MA-031/A96 (Determination of ketones (acetone, methyl ethyl ketone, methyl isobutyl ketone) in air - Charcoal tube method / Gas chromatography) - 1996 - EU project BC/CEN/ENTR/000/2002-16 card 105-1 (2004) - MDHS 72 (Volatile organic compounds in air – Laboratory method using pumped solid sorbent tubes, thermal desorption and gas chromatography) - 1993 - NIOSH 2500 (METHYL ETHYL KETONE) - 1996 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - NIOSH 2555 (KETONES I) - 2003 - NIOSH 3800 (ORGANIC AND INORGANIC GASES BY EXTRACTIVE FTIR SPECTROMETRY) - 2016 - OSHA 1004 (2-Butanone (MEK) Hexone (MIBK)) - 2000 | |
| BMGV: 70 µmol butan-2-one/l in urine, post shift (BMGV) | Other information: Sk |

| Chemical Name | 2-methoxy-1-methylethyl acetate | Content %:5-15 |
|--|---|----------------|
| WEL-TWA: 50 ppm (274 mg/m ³) (WEL), 50 ppm (275 mg/m ³) (EU) | WEL-STEL: 100 ppm (548 mg/m ³) (WEL), 100 ppm (550 mg/m ³) (EU) | --- |
| Monitoring procedures: - INSHT MTA/MA-024/A92 (Determination of esters II (1-methoxy-2-propyl acetate, 2-ethoxyethyl acetate) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 15-1 (2004) - NIOSH 2554 (GLYCOL ETHERS) - 2003 - OSHA 99 (Propylene Glycol Monomethyl Ethers/Acetates) - 1993 | | |
| BMGV: --- | Other information: Sk (WEL) | |

| Chemical Name | Polyisocyanate, aliphatic | Content %:5-10 |
|--|---|----------------|
| WEL-TWA: 0,02 mg/m ³ (Isocyanates, all (as -NCO)) | WEL-STEL: 0,07 mg/m ³ (Isocyanates, all (as -NCO)) | --- |
| Monitoring procedures: --- | | |
| BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure) | Other information: Sen (Isocyanates, all (as -NCO)) | |

| Chemical Name | n-butyl acetate | Content %:1-5 |
|--|---|---------------|
| WEL-TWA: 150 ppm (724 mg/m ³) (WEL), 50 ppm (241 mg/m ³) (EU) | WEL-STEL: 200 ppm (966 mg/m ³) (WEL), 150 ppm (723 mg/m ³) (EU) | --- |
| Monitoring procedures: - Compur - KITA-138 U (548 857) - Compur - KITA-139 SB(C) (549 731) - NIOSH 1450 (ESTERS 1) - 2003 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - OSHA 1009 (n-Butyl Acetate Isobutyl Acetate sec-Butyl Acetate tert-Butyl Acetate) - 2007 | | |
| BMGV: --- | Other information: --- | |

| Chemical Name | Xylene | Content %:1-5 |
|--|---|---------------|
| WEL-TWA: 220 mg/m ³ (50 ppm) (WEL), 50 ppm (221 mg/m ³) (EU) | WEL-STEL: 100 ppm (441 mg/m ³) (WEL), 100 ppm (442 mg/m ³) (EU) | --- |
| Monitoring procedures: - Draeger - Xylene 10/a (67 33 161) - Compur - KITA-143 SA (550 325) - Compur - KITA-143 SB (505 998) - INSHT MTA/MA-030/A92 (Determination of aromatic hydrocarbons (benzene, toluene, ethylbenzene, p-xylene, 1,2,4-trimethylbenzene) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 47-1 (2004) - NIOSH 1501 (HYDROCARBONS, AROMATIC) - 2003 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - OSHA 1002 (Xylenes (o-, m-, p-isomers) Ethylbenzene) - 1999 | | |
| BMGV: 650 mmol methyl hippuric acid/mol creatinine in urine, post shift (Xylene, o-, m-, p- or mixed isomers) (BMGV) | Other information: Sk (WEL) | |

| Chemical Name | Diphenylmethanediisocyanate, isomeres and homologues | Content %:0,5-<1 |
|--|---|------------------|
| WEL-TWA: 0,02 mg/m ³ (Isocyanates, all (as -NCO)) | WEL-STEL: 0,07 mg/m ³ (Isocyanates, all (as -NCO)) | --- |
| Monitoring procedures: - ISO 16702 (Workplace air quality – determination of total isocyanate groups in air using 2-(1-methoxyphenyl)piperazine and liquid chromatography) - 2007 - MDHS 25/4 (Organic isocyanates in air – Laboratory method using sampling either onto 2-(1-methoxyphenyl)piperazine coated glass fibre filters followed by solvent desorption or into impingers and analysis using high performance liquid chromatography) - 2015 | | |
| BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure) | Other information: Sen (Isocyanates, all (as -NCO)) | |

Page 7 of 22
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 10.03.2021 / 0020
Replacing version dated / version: 02.12.2020 / 0019
Valid from: 10.03.2021
PDF print date: 15.06.2021
Active Primer

| Chemical Name | Carbon black | Content %: |
|----------------------------|-------------------|------------------------|
| WEL-TWA: 3,5 mg/m3 | WEL-STEL: 7 mg/m3 | --- |
| Monitoring procedures: --- | | |
| BMGV: --- | | Other information: --- |

| Butanone | | | | | | |
|---------------------|---|------------------|------------|--------|--------------|----------------------------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - freshwater | | PNEC | 55,8 | mg/l | |
| | Environment - marine | | PNEC | 55,8 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 284,74 | mg/kg dw | |
| | Environment - sediment, marine | | PNEC | 284,7 | mg/kg dw | |
| | Environment - soil | | PNEC | 22,5 | mg/kg dw | |
| | Environment - sewage treatment plant | | PNEC | 709 | mg/l | |
| | Environment - sporadic (intermittent) release | | PNEC | 55,8 | mg/l | |
| | Environment - oral (animal feed) | | PNEC | 1000 | mg/kg | |
| Consumer | Human - dermal | Long term | DNEL | 412 | mg/kg bw/day | Overall assesment factor 2 |
| Consumer | Human - inhalation | Long term | DNEL | 106 | mg/m3 | Overall assesment factor 2 |
| Consumer | Human - oral | Long term | DNEL | 31 | mg/kg bw/day | Overall assesment factor 2 |
| Workers / employees | Human - dermal | Long term | DNEL | 1161 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Long term | DNEL | 600 | mg/m3 | |

| 2-methoxy-1-methylethyl acetate | | | | | | |
|---------------------------------|--|-----------------------------|------------|--------|-------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - freshwater | | PNEC | 0,635 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 3,29 | mg/kg | |
| | Environment - sediment, marine | | PNEC | 0,329 | mg/kg | |
| | Environment - soil | | PNEC | 0,29 | mg/kg | |
| | Environment - sewage treatment plant | | PNEC | 100 | mg/l | |
| | Environment - marine | | PNEC | 0,0635 | mg/l | |
| | Environment - water, sporadic (intermittent) release | | PNEC | 6,35 | mg/l | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 33 | mg/m3 | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 54,8 | mg/kg | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 1,67 | mg/kg | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 153,5 | mg/kg | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 275 | mg/m3 | |

Page 8 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0020
 Replacing version dated / version: 02.12.2020 / 0019
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Active Primer

| Polyisocyanate, aliphatic | | | | | | |
|---------------------------|--|------------------|------------|--------|-------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - freshwater | | PNEC | 0,127 | mg/l | |
| | Environment - marine | | PNEC | 0,0127 | mg/l | |
| | Environment - sediment | | PNEC | 266700 | mg/kg | |
| | Environment - soil | | PNEC | 53182 | mg/kg | |
| | Environment - sewage treatment plant | | PNEC | 38,28 | mg/l | |
| Workers / employees | Human - inhalation | Short term | DNEL | 1 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term | DNEL | 0,5 | mg/m3 | |

| n-butyl acetate | | | | | | |
|---------------------|--|------------------------------|------------|--------|--------------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - freshwater | | PNEC | 0,18 | mg/l | |
| | Environment - marine | | PNEC | 0,018 | mg/l | |
| | Environment - periodic release | | PNEC | 0,36 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 0,981 | mg/kg | |
| | Environment - sediment, marine | | PNEC | 0,0981 | mg/kg | |
| | Environment - soil | | PNEC | 0,0903 | mg/kg | |
| | Environment - sewage treatment plant | | PNEC | 35,6 | mg/l | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 3,4 | mg/kg | |
| Consumer | Human - inhalation | Short term, systemic effects | DNEL | 300 | mg/m3 | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 35,7 | mg/m3 | |
| Consumer | Human - inhalation | Short term, local effects | DNEL | 300 | mg/m3 | |
| Consumer | Human - inhalation | Long term, local effects | DNEL | 35,7 | mg/m3 | |
| Consumer | Human - dermal | Short term, systemic effects | DNEL | 6 | mg/kg bw/day | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 2 | mg/kg bw/day | |
| Consumer | Human - oral | Short term, systemic effects | DNEL | 2 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Short term, systemic effects | DNEL | 600 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 300 | mg/m3 | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 7 | mg/kg bw/d | |
| Workers / employees | Human - dermal | Short term, systemic effects | DNEL | 11 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Short term, local effects | DNEL | 600 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 300 | mg/m3 | |

| Xylene | | | | | | |
|---------------------|--|------------------|------------|-------|------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - freshwater | | PNEC | 0,327 | mg/l | |

Page 9 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0020
 Replacing version dated / version: 02.12.2020 / 0019
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Active Primer

| | | | | | | |
|---------------------|--------------------------------------|------------------------------|------|-------|--------------|--|
| | Environment - sediment, freshwater | | PNEC | 12,46 | mg/kg | |
| | Environment - soil | | PNEC | 2,31 | mg/kg | |
| | Environment - marine | | PNEC | 0,327 | mg/l | |
| | Environment - sediment, marine | | PNEC | 12,46 | mg/kg | |
| | Environment - sewage treatment plant | | PNEC | 6,58 | mg/l | |
| Consumer | Human - inhalation | Short term, local effects | DNEL | 174 | mg/m3 | |
| Consumer | Human - inhalation | Short term, systemic effects | DNEL | 174 | mg/m3 | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 108 | mg/kg bw/day | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 14,8 | mg/m3 | |
| Workers / employees | Human - inhalation | Short term, local effects | DNEL | 289 | mg/m3 | |
| Workers / employees | Human - inhalation | Short term, systemic effects | DNEL | 289 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 77 | mg/m3 | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 180 | mg/kg | |

| Carbon black | | | | | | |
|---------------------|--|-----------------------------|------------|-------|-------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - freshwater | | PNEC | 1 | mg/l | |
| | Environment - marine | | PNEC | 0,1 | mg/l | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 0,06 | mg/m3 | |

98 WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Page 10 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0020
 Replacing version dated / version: 02.12.2020 / 0019
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Active Primer

Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Chemical resistant protective gloves (EN 374).
 If applicable
 Protective gloves made of butyl (EN 374).
 Protective nitrile gloves (EN 374).
 Minimum layer thickness in mm:
 0,4
 Permeation time (penetration time) in minutes:
 > 480
 Protective Neoprene® / polychloroprene gloves (EN 374).
 Minimum layer thickness in mm:
 0,4
 Permeation time (penetration time) in minutes:
 > 480
 Protective hand cream recommended.
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 Normally not necessary.
 If OES or MEL is exceeded.
 Filter A2 P2 (EN 14387), code colour brown, white
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|----------------|
| Physical state: | Liquid |
| Colour: | Black |
| Odour: | Characteristic |
| Odour threshold: | Not determined |
| pH-value: | Not determined |
| Melting point/freezing point: | Not determined |
| Initial boiling point and boiling range: | 79 °C |
| Flash point: | -4 °C |
| Evaporation rate: | Not determined |
| Flammability (solid, gas): | n.a. |
| Lower explosive limit: | 1,8 Vol-% |
| Upper explosive limit: | 11,5 Vol-% |

Page 11 of 22
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 10.03.2021 / 0020
Replacing version dated / version: 02.12.2020 / 0019
Valid from: 10.03.2021
PDF print date: 15.06.2021
Active Primer

| | |
|--|---|
| Vapour pressure: | 105 hPa (20°C) |
| Vapour density (air = 1): | Not determined |
| Density: | 0,91 g/cm ³ (20°C) |
| Bulk density: | n.a. |
| Solubility(ies): | Not determined |
| Water solubility: | Not miscible |
| Partition coefficient (n-octanol/water): | Not determined |
| Auto-ignition temperature: | >300 °C (Ignition temperature) |
| Auto-ignition temperature: | No |
| Decomposition temperature: | Not determined |
| Viscosity: | Not determined |
| Explosive properties: | Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture. |
| Oxidising properties: | No |

9.2 Other information

| | |
|---------------------------|----------------|
| Miscibility: | Not determined |
| Fat solubility / solvent: | Not determined |
| Conductivity: | Not determined |
| Surface tension: | Not determined |
| Solvents content: | 72,3 % |

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Electrostatic charge

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

| Active Primer | | | | | | |
|---|----------|-------|------|----------|-------------|--------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | | | | | | n.d.a. |
| Acute toxicity, by dermal route: | | | | | | n.d.a. |
| Acute toxicity, by inhalation: | | | | | | n.d.a. |
| Skin corrosion/irritation: | | | | | | n.d.a. |
| Serious eye damage/irritation: | | | | | | n.d.a. |
| Respiratory or skin sensitisation: | | | | | | n.d.a. |
| Germ cell mutagenicity: | | | | | | n.d.a. |
| Carcinogenicity: | | | | | | n.d.a. |
| Reproductive toxicity: | | | | | | n.d.a. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | n.d.a. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | n.d.a. |

Page 12 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0020
 Replacing version dated / version: 02.12.2020 / 0019
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Active Primer

| | | | | | | |
|--------------------|--|--|--|--|--|--------|
| Aspiration hazard: | | | | | | n.d.a. |
| Symptoms: | | | | | | n.d.a. |

| Butanone | | | | | | |
|---|----------|-------|----------|------------------------|---|--|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >2000 | mg/kg | Rat | OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method) | |
| Acute toxicity, by dermal route: | LD50 | 5000 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | 34,5 | mg/l/4h | Rat | | |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Mild irritant, Repeated exposure may cause skin dryness or cracking. |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Eye Irrit. 2 |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | Not sensitising |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | Mouse | OECD 474 (Mammalian Erythrocyte Micronucleus Test) | Negative |
| Germ cell mutagenicity: | | | | Mouse | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative |
| Reproductive toxicity (Developmental toxicity): | NOAEC | 1002 | ppm | Rat | OECD 414 (Prenatal Developmental Toxicity Study) | Negative |
| Symptoms: | | | | | | respiratory distress, drowsiness, unconsciousness, drop in blood pressure, coughing, headaches, cramps, intoxication, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting., mental confusion, fatigue |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEC | 5041 | ppm/6h/d | Rat | OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study) | Vapours, Negative |

| 2-methoxy-1-methylethyl acetate | | | | | | |
|----------------------------------|----------|-------|---------|----------|--|--------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rabbit | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >5000 | mg/kg | Rat | | |
| Acute toxicity, by inhalation: | LC50 | >23,8 | mg/l/6h | Rat | | |
| Acute toxicity, by inhalation: | LC50 | 35,7 | mg/l/4h | Rat | | Vapours |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |

Page 13 of 22
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 10.03.2021 / 0020
Replacing version dated / version: 02.12.2020 / 0019
Valid from: 10.03.2021
PDF print date: 15.06.2021
Active Primer

| | | | | | | |
|------------------------------------|--|--|--|------------|--|---|
| Serious eye damage/irritation: | | | | Rabbit | | Mild irritant |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | No (skin contact) |
| Germ cell mutagenicity: | | | | | OECD 471 (Bacterial Reverse Mutation Test) | No indications of such an effect. |
| Symptoms: | | | | | | respiratory distress, drowsiness, unconsciousness, vomiting, headaches, mucous membrane irritation, dizziness, nausea |

| Polyisocyanate, aliphatic | | | | | | |
|---|----------|-------|-------|------------------------|---|-------------------------------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >2500 | mg/kg | Rat | OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method) | |
| Acute toxicity, by inhalation: | LC50 | 1-5 | mg/l | | | Expert judgement |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Slightly irritant |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Slightly irritant |
| Respiratory or skin sensitisation: | | | | Mouse | OECD 429 (Skin Sensitisation - Local Lymph Node Assay) | Sensitising (skin contact) |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | Sensitising (skin contact) |
| Germ cell mutagenicity: | | | | | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | Mammalian | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative |
| Reproductive toxicity: | | | | | | Negative |
| Specific target organ toxicity - single exposure (STOT-SE), inhalative: | | | | | | Irritation of the respiratory tract |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOEL | 4,3 | mg/m3 | Rat | OECD 412 (Subacute Inhalation Toxicity - 28-Day Study) | |

| n-butyl acetate | | | | | | |
|----------------------------------|----------|--------|---------|----------|---|--------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | 10760 | mg/kg | Rat | OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method) | |
| Acute toxicity, by dermal route: | LD50 | >14112 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | 21,1 | mg/l/4h | Rat | OECD 403 (Acute Inhalation Toxicity) | Mist |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant |

Page 14 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0020
 Replacing version dated / version: 02.12.2020 / 0019
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Active Primer

| | | | | | | |
|---|-------|------|-------|------------------------|---|---|
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | No (skin contact) |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Reproductive toxicity: | NOAEC | 9640 | mg/m3 | | OECD 416 (Two-generation Reproduction Toxicity Study) | Negative |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | Vapours may cause drowsiness and dizziness. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | Negative |
| Symptoms: | | | | | | drowsiness, unconsciousness, headaches, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting. |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEC | 500 | ppm | Rat | | |
| Other information: | | | | | | Repeated exposure may cause skin dryness or cracking. |

| Xylene | | | | | | |
|------------------------------------|----------|-------|---------|----------|--------------|--|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | 2840 | mg/kg | Rat | | |
| Acute toxicity, by dermal route: | LD50 | >1700 | mg/kg | Rabbit | | |
| Acute toxicity, by inhalation: | LC50 | 21,7 | mg/l/4h | Rat | | Vapours, Does not conform with EU classification. |
| Skin corrosion/irritation: | | | | Rabbit | | Irritant |
| Serious eye damage/irritation: | | | | Rabbit | | Slightly irritant |
| Respiratory or skin sensitisation: | | | | | (Patch-Test) | Negative |
| Symptoms: | | | | | | breathing difficulties, drying of the skin., drowsiness, unconsciousness, burning of the membranes of the nose and throat, vomiting, skin afflictions, heart/circulatory disorders, coughing, headaches, drowsiness, dizziness, nausea |

Page 15 of 22
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 10.03.2021 / 0020
Replacing version dated / version: 02.12.2020 / 0019
Valid from: 10.03.2021
PDF print date: 15.06.2021
Active Primer

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|---|----------|-------|---------|----------|-------------|--|
| Acute toxicity, by inhalation: | LC50 | 0,493 | mg/l/4h | Rat | | Does not conform with EU classification. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | Irritation of the respiratory tract |
| Aspiration hazard: | | | | | | No |

| Carbon black | | | | | | |
|---|----------|--------|-------|------------|--|--------------------------------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >2000 | mg/kg | Rat | | |
| Acute toxicity, by dermal route: | LD50 | >3000 | mg/kg | | | |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | Not sensitising |
| Germ cell mutagenicity: | | | | | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Carcinogenicity: | | | | Mouse | | Negative |
| Specific target organ toxicity - repeated exposure (STOT-RE): | NOEL | 0,0011 | mg/l | | | References, Target organ(s): lung90d |
| Aspiration hazard: | | | | | | No |
| Specific target organ toxicity - repeated exposure (STOT-RE), oral: | NOAEL | 137 | mg/kg | Mouse | | |
| Specific target organ toxicity - repeated exposure (STOT-RE), oral: | NOAEL | 52 | mg/kg | Rat | | |

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

| Active Primer | | | | | | | |
|--|----------|------|-------|------|----------|-------------|---|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | | | | | | | n.d.a. |
| 12.1. Toxicity to daphnia: | | | | | | | n.d.a. |
| 12.1. Toxicity to algae: | | | | | | | n.d.a. |
| 12.2. Persistence and degradability: | | | | | | | With water at the interface, transforms slowly with formation of CO2 into a firm, insoluble reaction product with a high melting point (polycarbamide). According to experience available to date, polycarbamide is inert and non-degradable. |
| 12.3. Bioaccumulative potential: | | | | | | | n.d.a. |
| 12.4. Mobility in soil: | | | | | | | n.d.a. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | n.d.a. |

Page 16 of 22
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 10.03.2021 / 0020
Replacing version dated / version: 02.12.2020 / 0019
Valid from: 10.03.2021
PDF print date: 15.06.2021
Active Primer

| | | | | | | | |
|------------------------------|--|--|--|--|--|--|--|
| 12.6. Other adverse effects: | | | | | | | n.d.a. |
| Other information: | | | | | | | According to the recipe, contains no AOX. |
| Other information: | | | | | | | DOC-elimination degree(complexing organic substance)>= 80%/28d: n.a. |

| Butanone | | | | | | | |
|--|-----------|------|-----------|------|---------------------------------|--|---|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No vPvB substance, No PBT substance |
| 12.1. Toxicity to fish: | LC50 | 96h | 1690 | mg/l | Lepomis macrochirus | | |
| 12.1. Toxicity to fish: | LC50 | 96h | 2993 | mg/l | Pimephales promelas | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | 308 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | LC50 | 72h | 1972 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.1. Toxicity to algae: | ErC50 | 96h | 2029 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | 28d | 98 | % | | OECD 301 D (Ready Biodegradability - Closed Bottle Test) | Readily biodegradable |
| 12.3. Bioaccumulative potential: | Log Pow | | 0,29 | | | OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method) | Bioaccumulation is unlikely (LogPow < 1). |
| 12.4. Mobility in soil: | H (Henry) | | 0,0000244 | | | | 25°C |
| 12.4. Mobility in soil: | Log Koc | | 3,8 | | | | |
| Toxicity to bacteria: | EC0 | 16h | 1150 | mg/l | Pseudomonas putida | DIN 38412 T.8 | |
| Other information: | DOC | | >70 | % | | | |
| Other information: | BOD/COD | | >50 | % | | | |

| 2-methoxy-1-methylethyl acetate | | | | | | | |
|---------------------------------|-----------|------|---------|------|---------------------|--|-------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | LC50 | 96h | 100-180 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | >500 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to daphnia: | NOEC/NOEL | 21d | >100 | mg/l | Daphnia magna | OECD 211 (Daphnia magna Reproduction Test) | |

Page 17 of 22
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 10.03.2021 / 0020
Replacing version dated / version: 02.12.2020 / 0019
Valid from: 10.03.2021
PDF print date: 15.06.2021
Active Primer

| | | | | | | | |
|--|------|-------|-------|------|------------------|--|-------------------------------------|
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| Toxicity to bacteria: | EC20 | 30min | >1000 | mg/l | activated sludge | OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation)) | |

| Polyisocyanate, aliphatic | | | | | | | |
|--|-----------|------|-----------|-----------|-------------------------|--|-------------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | LC50 | 96h | >100 | mg/l | Brachydanio rerio | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | EC10 | 48h | >100 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | IC50 | 72h | >100 | mg/l | Scenedesmus subspicatus | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | 28d | 0 | % | | OECD 301 C (Ready Biodegradability - Modified MITI Test (I)) | Not readily biodegradable |
| 12.4. Mobility in soil: | H (Henry) | | <0,000001 | Pa*m3/mol | | | 25°C |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| Toxicity to bacteria: | EC50 | 3h | >1000 | mg/l | | OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation)) | Activated sludge |

| n-butyl acetate | | | | | | | |
|----------------------------------|-----------|------|-------|------|-------------------------|--|--------------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.6. Other adverse effects: | | | | | | | Product floats on the water surface. |
| 12.3. Bioaccumulative potential: | BCF | | 15,3 | | | | |
| 12.1. Toxicity to fish: | LC50 | 96h | 18 | mg/l | Pimephales promelas | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | 44 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to daphnia: | NOEC/NOEL | 21d | 23 | mg/l | Daphnia magna | OECD 211 (Daphnia magna Reproduction Test) | |
| 12.1. Toxicity to algae: | EC50 | 72h | 397 | mg/l | Scenedesmus subspicatus | OECD 201 (Alga, Growth Inhibition Test) | |

Page 18 of 22
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 10.03.2021 / 0020
Replacing version dated / version: 02.12.2020 / 0019
Valid from: 10.03.2021
PDF print date: 15.06.2021
Active Primer

| | | | | | | | |
|--|-----------|-----|----------|------|-------------------------|--|-------------------------------------|
| 12.1. Toxicity to algae: | NOEC/NOEL | 72h | 200 | mg/l | Desmodesmus subspicatus | | |
| 12.2. Persistence and degradability: | | 28d | 98 | % | | OECD 301 D (Ready Biodegradability - Closed Bottle Test) | Readily biodegradable |
| 12.3. Bioaccumulative potential: | Log Pow | | 1,81-2,3 | | | | Low |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| Toxicity to bacteria: | EC10 | | 959 | mg/l | Pseudomonas putida | | |

| Xylene | | | | | | | |
|--------------------------------------|----------|------|--------|------|---------------------|-------------|-----------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | LC50 | 96h | 86 | mg/l | Leuciscus idus | | |
| 12.1. Toxicity to fish: | LC50 | 96h | 8,2 | mg/l | Oncorhynchus mykiss | | |
| 12.1. Toxicity to daphnia: | EC50 | 24h | 75,5 | mg/l | Daphnia magna | | |
| 12.1. Toxicity to algae: | IC50 | 72h | 10 | mg/l | | | |
| 12.2. Persistence and degradability: | | | | | | | Readily biodegradable |
| 12.3. Bioaccumulative potential: | Log Pow | | >3 | | | | |
| 12.3. Bioaccumulative potential: | BCF | | 0,6-15 | | | | |

| Carbon black | | | | | | | |
|--------------------------------------|-----------|------|-------|------|-------------------------|--|---|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| Water solubility: | | | | | | | Insoluble, Product floats on the water surface. |
| 12.1. Toxicity to fish: | LC50 | 96h | >1000 | mg/l | Brachydanio rerio | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | EC50 | 24h | >5600 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | NOEC/NOEL | 3d | 10000 | mg/l | Scenedesmus subspicatus | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | | | | | | Not biodegradable |
| 12.3. Bioaccumulative potential: | | | | | | | Not to be expected |
| Toxicity to bacteria: | EC0 | 3h | >=800 | mg/l | activated sludge | Regulation (EC) 440/2008 C.22 (SOIL MICROORGANISMS - CARBON TRANSFORMATION TEST) | |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

Page 19 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0020
 Replacing version dated / version: 02.12.2020 / 0019
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Active Primer

The waste codes are recommendations based on the scheduled use of this product.
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)
 08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances
 Recommendation:
 Sewage disposal shall be discouraged.
 Pay attention to local and national official regulations.
 E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.
 15 01 01 paper and cardboard packaging
 15 01 02 plastic packaging
 15 01 04 metallic packaging
 Empty container completely.
 Uncontaminated packaging can be recycled.
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: 1866

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:
 UN 1866 RESIN SOLUTION
 14.3. Transport hazard class(es): 3
 14.4. Packing group: II
 Classification code: F1
 LQ: 5 L
 14.5. Environmental hazards: Not applicable
 Tunnel restriction code: D/E



Transport by sea (IMDG-code)

14.2. UN proper shipping name:
 RESIN SOLUTION
 14.3. Transport hazard class(es): 3
 14.4. Packing group: II
 EmS: F-E, S-E
 Marine Pollutant: n.a.
 14.5. Environmental hazards: Not applicable



Transport by air (IATA)

14.2. UN proper shipping name:
 Resin solution
 14.3. Transport hazard class(es): 3
 14.4. Packing group: II
 14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Page 20 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0020
 Replacing version dated / version: 02.12.2020 / 0019
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Active Primer

Regulation (EC) No 1907/2006, Annex XVII
 Polyisocyanate, aliphatic
 Diphenylmethanediisocyanate, isomeres and homologues
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

| Hazard categories | Notes to Annex I | Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements | Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements |
|-------------------|------------------|---|---|
| P5c | | 5000 | 50000 |

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 72,34 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2, 15

Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

| Classification in accordance with regulation (EC) No. 1272/2008 (CLP) | Evaluation method used |
|---|--|
| Flam. Liq. 2, H225 | Classification based on test data. |
| Eye Irrit. 2, H319 | Classification according to calculation procedure. |
| Resp. Sens. 1, H334 | Classification according to calculation procedure. |
| Skin Sens. 1, H317 | Classification according to calculation procedure. |
| STOT SE 3, H336 | Classification according to calculation procedure. |

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H373 May cause damage to organs through prolonged or repeated exposure by inhalation.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H351 Suspected of causing cancer.

Flam. Liq. — Flammable liquid
 Eye Irrit. — Eye irritation
 Resp. Sens. — Respiratory sensitization

Page 21 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.03.2021 / 0020
 Replacing version dated / version: 02.12.2020 / 0019
 Valid from: 10.03.2021
 PDF print date: 15.06.2021
 Active Primer

Skin Sens. — Skin sensitization
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects
 Acute Tox. — Acute toxicity - inhalation
 STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation
 Acute Tox. — Acute toxicity - dermal
 Skin Irrit. — Skin irritation
 Carc. — Carcinogenicity
 STOT RE — Specific target organ toxicity - repeated exposure

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ASTM ASTM International (American Society for Testing and Materials)
 ATE Acute Toxicity Estimate
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BSEF The International Bromine Council
 bw body weight
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 etc. et cetera
 EU European Union
 EVAL Ethylene-vinyl alcohol copolymer
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC (Code) International Bulk Chemical (Code)
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 IUPAC International Union for Pure Applied Chemistry
 LC50 Lethal Concentration to 50 % of a test population
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 OECD Organisation for Economic Co-operation and Development
 org. organic
 PBT persistent, bioaccumulative and toxic

Page 22 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.03.2021 / 0020

Replacing version dated / version: 02.12.2020 / 0019

Valid from: 10.03.2021

PDF print date: 15.06.2021

Active Primer

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.