

Page 1 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.04.2019 / 0018 Replacing version dated / version: 29.06.2018 / 0017 Valid from: 10.04.2019 PDF print date: 14.06.2021 Silikonspray

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Silikonspray

ആ

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Eluent Lubricant Sector of use [SU]: SU21 - Consumer uses: Private households (=general public = consumers) SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Chemical product category [PC]: PC24 - Lubricants, greases, release products Process category [PROC]: PROC11 - Non industrial spraying Environmental Release Category [ERC]: ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 8d - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) **Uses advised against:**

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)							
Hazard class	Hazard category	Hazard statement					
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.					
Aerosol	1	H222-Extremely flammable aerosol.					
Aerosol	1	H229-Pressurised container: May burst if heated.					

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 13

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.04.2019 / 0018 Replacing version dated / version: 29.06.2018 / 0017 Valid from: 10.04.2019 PDF print date: 14.06.2021 Silikonspray



Danger

H412-Harmful to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

Without adequate ventilation, formation of explosive mixtures may be possible.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

SECTION 3: Composition/information on ingredients

Aerosol 3.1 Substances

n.a. 3.2 Mixtures

5.2 MIXtures	
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	
Registration number (REACH)	01-2119473851-33-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	920-750-0
CAS	
content %	2,5-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225
	Asp. Tox. 1, H304
	STOT SE 3, H336
	Aquatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area. Supply person with fresh air and consult doctor according to symptoms.



Page 3 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.04.2019 / 0018 Replacing version dated / version: 29.06.2018 / 0017 Valid from: 10.04.2019 PDF print date: 14.06.2021 Silikonspray

If the person is unconscious, place in a stable side position and consult a doctor. Respiratory arrest - Artificial respiration apparatus necessary.

Skin contact

œ

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses. Wash thoroughly for several minutes using copious water. Seek medical help if necessary. Consult medical specialist.

Ingestion

Typically no exposure pathway. Rinse the mouth thoroughly with water. Immediate admittance to a hospital.

4.2 Most important symptoms and effects, both acute and delayed

Irritation of the respiratory tract Irritation of the skin. Irritation of the eyes Headaches Dizziness Effects/damages the central nervous system Coordination disorders fatigue Unconsciousness With long-term contact: Drying of the skin. Dermatitis (skin inflammation) Other dangerous properties cannot be ruled out. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. **4.3 Indication of any immediate medical attention and special treatment needed**

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2 Sand Extinction powder Water jet spray Foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Danger of explosion by prolonged heating. Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.



Page 4 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.04.2019 / 0018 Replacing version dated / version: 29.06.2018 / 0017 Valid from: 10.04.2019 PDF print date: 14.06.2021 Silikonspray

Ensure sufficient supply of air.

ആ

Avoid inhalation, and contact with eyes or skin.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous. Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available. Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling 7.1.1 General recommendations

Ensure good ventilation.

Do not use the product in enclosed spaces.

Keep away from sources of ignition - Do not smoke. Do not use on hot surfaces. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use. Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals. Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Observe special regulations for aerosols!

Observe special storage conditions.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place. 7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 1200 mg/m3

^(B) Chemical Name	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Content %:2,5- <10	
WEL-TWA: 1200 mg/m3	WEL-STEL:		
Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571)		
	 Draeger - Hydrocarbons 2/a (81 03 581) 		
	- Compur - KITA-187 S (551 174)		
BMGV:	Other information: (O paragraphs 84-87, EH4		o RCP-method,
Chemical Name	Hydrocarbons, C3-4		Content %:
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: 1250 ppm (2180 mg/m3) (Liquefied petroleum gas (LPG))		
Monitoring procedures:			



Page 5 of 13

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.04.2019 / 0018 Replacing version dated / version: 29.06.2018 / 0017 Valid from: 10.04.2019 PDF print date: 14.06.2021 Silikonspray

BMGV: ---

Other information: ---

Hydrocarbons, C7-C9, n-a	alkanes, isoalkanes, cyclics					
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: With danger of contact with eyes. Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN 374). Recommended Protective nitrile gloves (EN 374). Minimum layer thickness in mm: 0,65 Permeation time (penetration time) in minutes: > 120 Protective hand cream recommended.



Page 6 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.04.2019 / 0018 Replacing version dated / version: 29.06.2018 / 0017 Valid from: 10.04.2019 PDF print date: 14.06.2021 Silikonspray

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. In case of emergency: Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Thermal hazards: Not applicable

ആ

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Dhysical state:	• •
Physical state: Colour:	Aerosol. Active substance: liquid. Colourless
Odour:	Colouriess Characteristic
Odour: Odour threshold:	
	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	Not determined
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	0,9 Vol-%
Upper explosive limit:	9,5 Vol-% (Propane)
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,595 g/ml
Bulk density:	n.a.
Solubility(ies):	Alcohols, Hydrocarbons
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	n.a.
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive. Possible build up of explosive/highly
	flammable vapour/air mixture.
Oxidising properties:	Not determined
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity



Page 7 of 13

GB

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.04.2019 / 0018 Replacing version dated / version: 29.06.2018 / 0017 Valid from: 10.04.2019 PDF print date: 14.06.2021 Silikonspray

10.1 Reactivity

The product has not been tested. Not to be expected

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No decomposition if used as intended.

10.4 Conditions to avoid

See also section 7. Heating, open flame, ignition sources Pressure increase will result in danger of bursting.

10.5 Incompatible materials

See also section 7. Avoid contact with oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

....

No decomposition when used as directed.

07.00

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>2800	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>23,3	mg/l/4h	Rat	OECD 403 (Acute	Vapours
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Skin corrosion/irritation:						Repeated
						exposure may
						cause skin
						dryness or
						cracking.



- @
Page 8 of 13
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 10.04.2019 / 0018
Replacing version dated / version: 29.06.2018 / 0017
Valid from: 10.04.2019
PDF print date: 14.06.2021
Silikonspray

Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
				Guinea pig		
sensitisation:					Sensitisation)	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:		2000	mg/kg	Mouse	OECD 474 (Mammalian	Negative
					Erythrocyte	
					Micronucleus Test)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
3 7					Reverse Mutation Test)	5
Reproductive toxicity:					OECD 414 (Prenatal	Negative
					Developmental Toxicity	June
					Study)	
Reproductive toxicity:	LOAEL	9000	ppm	Rat	OECD 416 (Two-	Negative
Reproductive toxicity.	LOALL	5000	ppin	Rat	generation	Negative
					Reproduction Toxicity	
					Study)	
Specific target organ toxicity -					Sludy)	STOT SE 3,
						H336
single exposure (STOT-SE):						
Specific target organ toxicity -					OECD 413 (Subchronic	Negative
repeated exposure (STOT-RE):					Inhalation Toxicity - 90-	
					Day Study)	
Aspiration hazard:						Yes
Symptoms:						drowsiness,
						unconsciousnes
						,
						heart/circulatory
						disorders,
						headaches,
						cramps,
						drowsiness,
						mucous
						membrane
						irritation,
						dizziness,
						nausea and
						vomiting.

Hydrocarbons, C3-4						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Symptoms:						malaise, nausea,
						dizziness,
						mucous
						membrane
						irritation,
						drowsiness,
						unconsciousness

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Silikonspray							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	-						n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							



Page 9 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.04.2019 / 0018 Replacing version dated / version: 29.06.2018 / 0017 Valid from: 10.04.2019 PDF print date: 14.06.2021 Silikonspray

œ)

12.3. Bioaccumulative	n.d.a.
potential:	
12.4. Mobility in soil:	n.d.a.
12.5. Results of PBT	n.d.a.
and vPvB assessment	
12.6. Other adverse	n.d.a.
effects:	
Other information:	Classification
	according to
	calculation
	procedure.
	According to the
	recipe, contains
	no ÁOX.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.6. Other adverse effects:							Product floats or the water surface.
12.1. Toxicity to fish:	NOELR	28d	0,574		Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	3 - 10	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	4,6 - 10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	1 -1,6	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	10	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EL50	72h	10	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	98	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Completely biodegradable.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EL50	48h	11,14	mg/l			calculated value

Hydrocarbons, C3-4 Toxicity / effect Endpoint Time Value Unit Organism Test method Notes 12.4. Mobility in soil: Product is slightly volatile. Biodegradable 12.2. Persistence and degradability: 12.3. Bioaccumulative A notable biological potential: accumulation potential is not to be expected (LogPow 1-3). No PBT 12.5. Results of PBT substance, No and vPvB assessment vPvB substance



Page 10 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.04.2019 / 0018 Replacing version dated / version: 29.06.2018 / 0017 Valid from: 10.04.2019 PDF print date: 14.06.2021 Silikonspray

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

œ)

1
C Code
30



Page 11 of 13

അ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.04.2019 / 0018 Replacing version dated / version: 29.06.2018 / 0017 Valid from: 10.04.2019 PDF print date: 14.06.2021 Silikonspray

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for the	referred to in Article 3(10) for the
		application of - Lower-tier	application of - Upper-tier
		requirements	requirements
P3b	11.1, 11.2	5000 (netto)	50000 (netto)
The Materia to Assess 4 of Discretions (distribute the large have a stand state of C and	wether teles a lister encount with each

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

2, 15

548 g/l

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aquatic Chronic 3, H412	Classification according to calculation procedure.
Aerosol 1, H222	Classification based on test data.
Aerosol 1, H229	Classification based on test data.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Aquatic Chronic — Hazardous to the aquatic environment - chronic Aerosol — Aerosols Flam. Liq. — Flammable liquid Asp. Tox. — Aspiration hazard STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Any abbreviations and acronyms used in this document:



ആ Page 12 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.04.2019 / 0018 Replacing version dated / version: 29.06.2018 / 0017 Valid from: 10.04.2019 PDF print date: 14.06.2021 Silikonspray ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BAuA BSEF The International Bromine Council body weight bw CAS **Chemical Abstracts Service** Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances CLP and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. ЕČ European Community ECHA European Chemicals Agency EEC European Economic Community EINECS European Inventory of Existing Commercial Chemical Substances FI INCS European List of Notified Chemical Substances FN European Norms FPA United States Environmental Protection Agency (United States of America) et cetera etc. European Union EU EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number general gen. Globally Harmonized System of Classification and Labelling of Chemicals GHS GWP Global warming potential International Agency for Research on Cancer IARC International Air Transport Association IATA IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available OECD Organisation for Economic Co-operation and Development organic org. PBT persistent, bioaccumulative and toxic PE Polyethylene PNEC Predicted No Effect Concentration parts per million ppm Polyvinylchloride **PVC** REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Telephone Tel. UN RTDG United Nations Recommendations on the Transport of Dangerous Goods



Page 13 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.04.2019 / 0018 Replacing version dated / version: 29.06.2018 / 0017 Valid from: 10.04.2019 PDF print date: 14.06.2021 Silikonspray

VOC Volatile organic compounds very persistent and very bioaccumulative vPvB wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

GB

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.