

Printing date 11.05.2020 Version number 5 Revision: 01.04.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)

Article number: 03.9901-62xx.x / 7062xx

UFI: C600-606D-J00P-5FE4

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture hydraulic liquid

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Continental Aftermarket & Services GmbH

Sodener Straße 9

D-65824 Schwalbach am Taunus

Tel: +49-69-7603-11 Fax: +49-69-761061

Further information obtainable from:

Gefahrstoffmanagement Konzern, Zentrales Materiallabor

ate.sicherheit@contiautomotive.com

1.4 Emergency telephone number: NHS 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified according to the CLP regulation.

Hazard pictograms GHS08

Signal word Warning

Hazard-determining components of labelling:

Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

Hazard statements

H361d Suspected of damaging the unborn child.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood. P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

(Contd. on page 2)



Printing date 11.05.2020 Version number 5 Revision: 01.04.2020

Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)

vPvB: Not applicable.

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 30989-05-0 EINECS: 250-418-4 Reg.nr.: 01-2119462824-33-XXXX	Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate Repr. 2, H361d	≥70-<90%
CAS: 15520-05-5 EINECS: 239-555-0 Reg.nr.: 01-2120136161-71-XXXX	2,2'-(Octylimino)bisethanol Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Aquatic Chronic 3, H412	≥3-<10%
CAS: 111-46-6 EINECS: 203-872-2 Reg.nr.: 01-2119457857-21-XXXX	2,2'-oxybisethanol Acute Tox. 4, H302	<5%
CAS: 68442-68-2 EINECS: 270-485-3 Reg.nr.: 01-2120115789-46	Benzenamine, N-phenyl-, styrenated Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.1-<0.25%

SVHC

Does not contain any or < 0,1% SVHC according to Regulation (EC) No 1907/2006 (REACH), Article 57.

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Remove contaminated clothes and shoes immediately. **After inhalation:** Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

May be released in case of fire: CO, CO2, NOx.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

(Contd. on page 3)



Printing date 11.05.2020 Version number 5 Revision: 01.04.2020

Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)

Additional information

(Contd. of page 2)

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. **Information about fire - and explosion protection:** Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Storage at room temperature. Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

This product is hygroscopic.

Store in dry conditions.

Keep container tightly sealed.

Storage class according to TRGS 510: 10 combustible liquids.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

111-46-6 2,2'-oxybisethanol

WEL Long-term value: 101 mg/m³, 23 ppm

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

(Contd. on page 4)

(Contd. of page 3)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.05.2020 Version number 5 Revision: 01.04.2020

Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)

Respiratory protection:

Respiratory protection required in case of release of vapors / aerosols.

Use particulate filter with medium retention capacity for solid and liquid particles (eg EN 143 or 149, type P2 or FFP2).

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

Butyl caoutchouc (butyl rubber): minimum breakthrough time 480 min; minimum layer thickness: 0.7

NBR (nitrile rubber): minimum breakthrough time 30 min; minimum layer thickness: 0.4 mm

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Safety glasses

Body protection: Protective work clothing

Limitation and supervision of exposure into the environment

See section 6 and 7. No additional measures necessary.

Risk management measures

Use at industrial site in closed process with occasional controlled exposure or processes with equivalent containment conditions:

1 to 3 air changes per hour (90 % effectiveness) - basic standard of general ventilation

maximum 8 h exposure duration per day maximum 40 °C process temperature Use of functional fluids in small devices:

5 to 10 air changes per hour (70 % effectiveness) - good standard of controlled ventilation

maximum 8 h exposure duration per day maximum 40 °C process temperature

SECTION 9: Physical and chemical properties

9.1 information on ba	sic pnysicai and	a cnemicai	properties
General Information			

Appearance:

Form: Fluid
Colour: Yellow
Odour: Characteristic
Odour threshold: Not determined.

pH-value at 20 °C: 7-8 (FMVSS 116)

Change in condition

Melting point/freezing point: <-70 °C (DIN 51583) Initial boiling point and boiling range: >280 °C (FMVSS 116)

Flash point: 141 °C (ISO 2592 (open cup))

Flammability (solid, gas): Not applicable.

Ignition temperature: >200 °C (DIN 51794)

Decomposition temperature: 360 °C (Analogy)

(Contd. on page 5)



Printing date 11.05.2020 Version number 5 Revision: 01.04.2020

Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)

	(Contd. of page
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure at 20 °C:	<0.1 hPa
Density at 20 °C:	1.08 g/cm³ (DIN 51757)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
water at 20 °C:	350 g/l
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	17.5 mm²/s
Solvent content:	
Organic solvents:	2.0 %
Solids content:	0.0 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC5	0 valu	es relevant for classification:
30989-0)5-0 Tr	is[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate
Oral	LD50	>2,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
15520-0	5-5 2,2	2´-(Octylimino)bisethanol
Oral	LD50	1,157 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
		(Contd. on page 6)

(Contd. on page 6)



Printing date 11.05.2020 Version number 5 Revision: 01.04.2020

Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)

			(Contd. of page 5)	
			oxybisethanol	
	Oral	LD50	>5,000 mg/kg (rat)	
	Dermal	LD50	>5,000 mg/kg (rabbit)	
	68442-6	8-2 Be	enzenamine, N-phenyl-, styrenated	
Ī	Oral	LD50	>20,000 mg/kg (rat)	
	Dermal	LD50	>10,000 mg/kg (rabbit)	

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquati	c toxicity:
30989-	05-0 Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate
EC50	>100 mg/l (Algae) (72 h)
	>100 mg/l (daphnia) (48 h)
LC50	>100 mg/L (fish) (96 h)
15520-	05-5 2,2´-(Octylimino)bisethanol
EC50	1.35 mg/l (Algae) (OECD 201 72 h)
	>100 mg/l (bacteria) (OECD 209)
	19.1 mg/l (daphnia) (OECD 202 48 h)
LC50	22 mg/L (fish) (OECD 203 96 h)
111-46	-6 2,2'-oxybisethanol
EC50	>100 mg/l (Algae)
	>100 mg/l (daphnia) (DIN 38412 T.11)
LC50	>100 mg/L (fish) (96 h)
68442-	68-2 Benzenamine, N-phenyl-, styrenated
EC50	920 mg/l (fish)
NOEC	0.02 mg/L (daphnia) (OECD 211 21 d)
40 0 D	preistance and degradability. No further relevant information available

12.2 Persistence and degradability No further relevant information available.

Other information: The product is easily biodegradable.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Contd. on page 7)



Printing date 11.05.2020 Version number 5 Revision: 01.04.2020

Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)

(Contd. of page 6)

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment Not applicable.

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Disposal should be based on the relevant state and local laws and regulations, the disposal process should avoid pollution of the environment.

Recommendation

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

European	waste catalogue
16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST
16 01 00	end-of-life vehicles from different means of transport (including off-road machinery) and wastes from dismantling of end-of-life vehicles and vehicle maintenance (except 13, 14, 16 06 and 16 08)
16 01 13*	brake fluids

Uncleaned packaging:

Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN-Number		
ADR, IMDG, IATA	UN-	
ADN	Void	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
44.4 Dooking group		
14.4 Packing group	V-:-	
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Anna	ex II of	
Marpol and the IBC Code	Not applicable.	
UN "Model Regulation":	Void	



Printing date 11.05.2020 Version number 5 Revision: 01.04.2020

Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)

(Contd. of page 7)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

National regulations:

Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients are listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H361d Suspected of damaging the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Recommended restriction of use For industrial or professional purposes only.

Department issuing SDS:

Gefahrstoffmanagement Konzern

ate.sicherheit@contiautomotive.com

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent. Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - oral - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Repr. 2: Reproductive toxicity - Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Sources

http://echa.europa.eu/information-on-chemicals/cl-inventory

http://echa.europa.eu/web/guest/information-on-chemicals/registered-substances

http://www.reach-clp-biozid-helpdesk.de/de/Downloads/CLP-VO/CLP VO Anhang VI Tabelle 3 2.pdf

http://www.safeworkaustralia.gov.au/

(Contd. on page 9)

Page 9/9



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.05.2020 Version number 5 Revision: 01.04.2020

Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)

* Data compared to the previous version altered.

(Contd. of page 8)

GB -